Model Checking Concurrent Systems with Unbounded Integer Variables: Symbolic Representations, Approximations and Experimental Results*†

Tevfik Bultan, Richard Gerber and William Pugh
Department of Computer Science
University of Maryland, College Park, MD 20742, USA
{bultan,rich,pugh}@cs.umd.edu

Abstract

Model checking is a powerful technique for analyzing large, finite-state systems. In an infinite-state system, however, many basic properties are undecidable. In this paper, we present a new symbolic model checker which conservatively evaluates safety and liveness properties on infinite-state programs. We use Presburger formulas to symbolically encode a program's transition system, as well as its model-checking computations. All fixpoint calculations are executed symbolically, and their convergence is guaranteed by using approximation techniques. We demonstrate the promise of this technology on some well-known infinite-state concurrency problems.

1 Introduction

In recent years, there has been a surge of progress in the area of automated analysis for finite-state systems. Several reasons for this success are: (1) the development of powerful techniques such as *model-checking* (e.g., [6, 8]), which can efficiently verify safety and liveness properties; (2) innovative new data structures that symbolically encode large sets of states in compact formats (e.g., [5, 6, 25]); and (3) new ways of carrying out *compositional* and *local* analysis, to assuage the "state explosion" usually associated with concurrency (e.g., [7, 10, 18]). But when transition systems are not restricted to be finite, most of these techniques are no longer applicable, as they inherently depend on all underlying types being bounded. Also, general safety and liveness properties become undecidable for infinite transition systems.

We have developed a symbolic model checker to attack this problem, which is based on the following key concepts:

- Symbolically encoding transition relations and sets of states using affine constraints on integer variables, logical connectives and quantifiers (i.e., Presburger formulas).

*Preliminary results from this paper appeared as an extended abstract in the Proceedings of the 9th Conference on Computer Aided Verification (CAV '97).

†This work was supported in part by ONR grant N00014-94-10228, NSF CCR-9619808 and a Packard Fellowship.



Figure 1: Overview of the Analysis Tool.

- Efficiently manipulating these formulas (via a fast Presburger solver called the Omega library [21, 28]) to derive truth sets of temporal logic formulas and their fixpoint computations.
- Using conservative approximation techniques in analysis of infinite state programs, which guarantee convergence by allowing false negatives.

In any computer system variables are eventually mapped to finite representations. Thus, it might be argued that integer variables can be given a finite range, and programs can then be analyzed as finite-state machines – for example, using BDD's [6, 25]. For several reasons, however, this may not always be the best way to proceed. First, mapping integer variables and operations to their binary implementations may lead to highly inefficient static analysis. More importantly, one may wish to analyze an algorithm as an abstraction, and prove its correctness in a general sense for any implementation of integers.

Given a finite but very large transition system, an analysis technique which has a worst case complexity proportional to the size of the input transition system will run out of resources (i.e., memory) when the worst case is realized. Complexity analysis of model checking for all interesting temporal logics shows that worst case complexity is at least linear in the size of the input transition system. I.e., although model checking finite state systems is decidable (as opposed to infinite state systems) for very large systems it can be intractable. Hence, from a practical stand point, our techniques for analyzing infinite state systems can be viewed as techniques for analyzing very large finite state systems which do not rely on the finiteness of the state space.

In this paper we demonstrate our model checker's effectiveness on some classical infinite-state programs taken from the concurrency literature [3, 30]. While relatively small, they possess some interesting subtleties, especially in the tricky way their infinite-state variables influence control flow.

A summary of our approach is shown in Figure 1, and it depicts how we structure the three main phases: *translation*, *partitioning* and *analysis*.

In the *translation phase*, the system accepts as input a program written in a simple event action language; then it produces the corresponding set of Presburger relations. These Presburger relations are just a symbolic encoding of the program's underlying transition relation.

In the *partitioning phase*, the program's states and transitions are segregated into a set of partition classes, with the objective of reducing the complexity of verification. The motivation here is easy to understand: Consider treating a complex program as a single relation, which might contain multiple if-then-else branches and loops. Then consider pushing through a nontrivial weakest-precondition transform – say, to automatically derive a loop-invariant. In most cases, the result will explode into an unmanageable (potentially infinite) number of constraints. It is true that the general form of our verification problem is undecidable; hence, we cannot eliminate this issue entirely. However, partitioning lets us damp some of its effects – and more importantly, it increases the precision of our conservative techniques. The "default" partitioning strategies are:

- *DNF Partitioning:* This method decomposes the program's transition relation into a disjunctive-normal-form; then pre- and post-condition transforms are carried out for each disjunct, one at a time.
- *Control-Point Partitioning:* This method symbolically decomposes the state-space into partition classes, based on valuations of selected variables (we call these *control-points*).
- *Event-Domain Partitioning:* This method is a finer-grained version of Control-Point Partitioning. It forms its partition classes based on the enabling conditions of events so that in each partition class an event is either enabled for all states or disabled for all states.

We describe these strategies in the following sections. However, we stress two points here: (a) they are used to segregate the program (and its states) into large regions, which distinguish the truth or falsity of crucial temporal properties; and (b) these decompositions do not alter the underlying transition relation of the original program; hence, they preserve all temporal properties.

In the *analysis phase*, verification procedures are applied to help prove (or disprove) properties of interest. Many of these are inter-dependent; i.e., they automatically "call" each other as "subroutines" to obtain the original goal. Nonetheless, many high-level strategy decisions are left to the user. In the sequel, we demonstrate situations in which human input can help; specifically, we show a set of programs (and requirements) which helped reveal the relative strengths and weaknesses of each approach. While some programs were easily verified with certain strategies, the same strategies diverged when used on other programs. We note, however, that the user need not be a model-checking "expert" *per se*; rather, the type of experience we consider useful is more like that a programmer draws on when setting compiler-optimization levels.

As for the techniques, all of the "top-level" techniques we report are *at least* conservative, and several are exact. Some programs can, in fact, be quickly verified using exact symbolic model-checking algorithms, similar to those presented in [25] for BDDs. In our domain, the analogue of a CTL "atomic proposition" is postulated over the Presburger logic, and is propagated through the program as such. We supply both *backward* and *forward* procedures for exact analysis. (The backward version starts with the desired goal, and performs recursive pre-condition transforms to get back to the initial states; the forward procedure works in the opposite fashion.) Additionally, we export conservative variants of the backward and forward techniques, which can obtain lower and upper approximations to the exact fixpoint. Two of the methods use a generalized form of "widening" technique discussed in [13] for abstract interpretation. We demonstrate how the approximate methods work together (with minimal user intervention); i.e., how our driver program integrates lower and upper bounds for sub-formulas, and then derives a conservative result for the high-level goal.

Finally, we describe two procedures which can be run as a pre-processing step before model-checking. These will often accelerate convergence for *all* of the fixpoint techniques, both approximate and exact. One technique derives an upper bound for the program's reachable state space; the other is a related function which approximates the transitive closure of the transition relation. Both methods are guaranteed to converge, and both are used for the following purposes: (1) to reduce the sizes of the Presburger formulas generated during model-checking; and (2) to increase the precision of approximate analysis.

The remainder of the paper is organized as follows. In the following section we overview some related work in the field. Then, we present the syntax and semantics for concurrent programs and their properties. After introducing the Presburger encodings and partitioning techniques, we describe our symbolic model checker, and show how it exploits the Presburger representation. After formally defining *conservative approximations*, we discuss the specific approximation techniques for computing upper and lower bounds of fixpoints. Then, we present a variety of different example programs, and show how the various methods performed on them. Finally, we conclude with some discussion on our results.

2 Related Work

Other methods have been proposed to deal with infinite-state concurrent programs, and we note some of them here. In [9], Clarke *et al.* present a conservative model checking technique, by producing a finite abstraction of the program (e.g., via a congruence relation modulo a suitable integer), and then checking the property of interest on the abstraction. In [16], Dingel and Filkorn extend this method using "assumption-commitment" style reasoning and theorem proving. While these techniques require the user to find the appropriate abstractions – and hence are not completely automatable – we see them as being orthogonal to our approach. There may be cases where abstraction methods can vastly reduce the state space without achieving a finite representation. In these cases our model checker can be used on the infinite abstract models.

Another approach is to use symbolic execution technique [15, 19], which symbolically generates a program's execution paths. In practice, this method may end up generating an infinite number of nodes, and thus never terminate. This limitation can be overcome by having the user specify assertions about a process's behavior, which can be verified locally. Then the local proofs can be checked for cooperation [15]. Although this method has the benefit of incrementally proving correctness (as opposed to generating all possible interleavings), it relies on users to come up with the correct assertions.

Our work has some historical antecedents. Cooper [11] developed a technique which encodes transition relations as sets of Presburger formulas, and then converts queries about a program's properties to validity checks in Presburger arithmetic. The decision procedure used by Cooper was computationally very expensive which made the validity checks intractable. Also proving correctness as a single Presburger decision problem is not a method that can scale very well. We have found it more beneficial to use model checking as our primary technology, and use a Presburger solver for some subservient set-theoretic computations.

Our work was also influenced by known techniques from abstract interpretation [12, 13]; specifically, we use some approximation methods first developed for that domain. Most reachability properties can be formulated as least fixpoints over sets of a program's states; if the state space is infinite, these fixpoints may not be computable. Abstract interpretation provides a way of approximating these fixpoints via a technique known as "widening" – which can compute a least fixpoint's upper bound in finite time. Since our basic temporal operators require similar computations, we were able to successfully use this method in conjunction with the Omega library.

Our recursive approximation technique for temporal properties with nested temporal operators is similar to the one used by Kelb *et al.* in [20]. In [20] a temporal property expressed in mu-calculus is computed conservatively using two abstractions of the same program. One abstraction over estimates the behavior of the program and used for computing universal properties. Another abstraction underestimates the behavior of the program and is used for computing existential properties. Together they can be used to conservatively approximate any mu-calculus property. Similar methods are also used in [14, 27] where an approximation for a temporal formula expressed in mu-calculus is computed using lower or upper approximations of its subformulas. Our approximation techniques are based on approximating the fixpoint computations instead of approximating the program as a whole using abstractions. It is possible to use both of these techniques together.

Finally, our encoding of program states is similar to that used by Alur *et al.* in verifying hybrid systems [1, 2]. A hybrid system is a discrete control automaton, which interacts with continuously-changing, external parameters. Like us, Alur *et al.* used an application of widening to help solve verification queries over linear hybrid automata – in which transition relations are defined in terms of affine constraints over the variables of the system.

A fundamental difference between our work and the work of Alur *et al.* is that we encode sets of integers – as opposed to the real numbers used in hybrid systems – thus, we can use Presburger

Program: Unbounded Buffer		
Data Variables: p, c, q_1, q_2: positive integer		
Control Variables: $pc : \{Idle, Send\}$		
Initial Condition: $p = c = q_1 = q_2 = 0$		
Events:		
e_{IS}	**enabled:**	$pc = Idle$
	action:	$pc' = Send$
e_S	**enabled:**	$pc = Send$
	action:	$p' = p + 1 \wedge \ (q_1' = q_1 + 1 \ \vee \ q_2' = q_2 + 1)$
e_{SI}	**enabled:**	$pc = Send$
	action:	$pc' = Idle$
e_R	**enabled:**	$q_1 > 0 \vee q_2 > 0$
	action:	$(q_1 > 0 \wedge q_1' = q_1 - 1 \wedge c' = c + 1) \vee$
		$(q_2 > 0 \wedge q_2' = q_2 - 1 \wedge c' = c + 1)$

Figure 2: Example (UB) – Indexing for Two Unbounded Buffers.

formulas as our symbolic representation. This enables us to express and prove properties such as "*x is even*," using quantification. In general, satisfiability problems over constraints with integer variables are significantly harder to deal with. For example, checking to see if there exists an integer solution to a set of linear constraints is NP-hard, while the analogous real-valued problem can be solved in polynomial time.

3 Programs and Properties

We use the event-action language from [30] as our syntax for concurrent programs, with a semantics defined in terms of infinite transition systems. A concurrent program $C = (V, I, E)$ is represented by (1) a finite set of data and control variables V; (2) an initial condition I, which specifies the starting states of the program; and (3) a finite set of events E, where each event is considered atomic [30]. The state of a program is determined by the values of its data and control variables. We assume that the domain of each variable is a countable set. Each event is represented with an enabling condition and an action, where the enabling condition constrains the states in which the event can occur, and the action defines a transformation on the variables of the program.

Consider the concurrent program (UB) shown in Figure 2, which handles the counters for two unbounded buffers. Note that there is a single control variable pc which is used to attenuate the producer – and it can either be idle (i.e., $pc = Idle$) or ready-to-send (i.e., $pc = Send$). Alternatively, the consumer has only one event (e_R), which can execute whenever outstanding data is sitting in either of the buffers.

Four data variables are used to keep track of the the data items, from the perspective of the producer, the consumer and the two buffers. The total number of items produced (over the program's lifetime) is kept in the integer p; similarly, the number of items consumed is counted in variable c. The other two variables – q_1 and q_2 – keep track of the outstanding items in the buffers. Note that all the data variables can increase without bound, i.e., this program is not a finite-state program.

In our event-action language, if a variable v is used in an event, then the symbol v' denotes the new value of v after the action. (If v is not mentioned in the action of an event, then we assume that its value is not altered by that event.)

Three properties of interest are as follows:

- (UB1) The total number of items produced is equal to the number of items consumed, plus the number of items sitting in the two buffers.
- (UB2) If the sender is idle, the total number of items in the buffers monotonically decreases.
- (UB3) The number of items consumed never exceeds the number produced.

Given scale of the program, one need not possess extraordinary skills to understand that the properties are indeed true. Yet, while we may *know* that *this* program is correct, its infinite state space will overcome most contemporary automated analysis engines. Hence, it is easy to see how a larger, more complex program would, in fact, be inaccessible to a *both* a programmer's (informal) "what-if" checks, *and* to an automated finite-state analyzer.

Given a program $C = (V, I, E)$ in the above language, we model it as an infinite transition system $M = (S, I, X, L)$, where S is the set of states, I is the set of initial states, $X \subseteq S \times S$ is the transition relation (derived from the set of events E), and $L : S \times SF \rightarrow \{\mathsf{True}, \mathsf{False}\}$ is the valuation function for state formulas over the program's variables. (We define the set of state formulas SF below.) The set of states S is obtained by taking the Cartesian product of domains of all program variables, i.e., given a program with n variables $V = \{v_1, v_2, \ldots, v_n\}$, each state $s \in S$ corresponds to a valuation of all the variables of the program

$$s \equiv \bigwedge_{i=1}^{n} v_i = x_i$$

where $x_i \in \mathbf{domain}(v_i)$.

Every event $e \in E$ defines a binary relation on the program's states, $X_e \subseteq S \times S$, interpreted as follows: If $(s, s') \in X_e$, then s and s' denote program's states before and after the execution of event e, respectively. We define the domain and range of an event e as:

$$\mathbf{domain}(e) = \{\ s \mid \exists (s, s')\ :\ (s, s') \in X_e\} \qquad \mathbf{range}(e) = \{\ s' \mid \exists (s, s')\ :\ (s, s') \in X_e\}$$

The global transition relation is $X \equiv \bigvee_{e \in E} X_e$. Note that we use an interleaving model, where each transition represents execution of a single event, i.e., only one event can occur at a time.

Presburger Formulas. Recall requirement (UB3) above, which asserts that the following property stays invariant over all executions: $p \geq c$. We call this type of assertion a *state formula*. And in general, we define the set of state formulas SF for a program C as the Presburger formulas generated by the following grammar:

$$f \ ::= \ t \leq t \mid (f) \mid f \wedge f \mid \neg f \mid \exists \ \textbf{intvar} \ (f) \qquad t \ ::= \ (t) \mid t + t \mid \textbf{intvar} \mid \textbf{intcons}$$

Here, the terminals **intcons** and **intvar** represent integer constants and variables, respectively. Using this base language, we can easily represent formulas including $<$, $=$, $\vee$, $\forall$, as well as multiplication by a constant. The set of closed formulas defined by the above grammar forms the theory of integers with addition, called *Presburger arithmetic*. An important property of Presburger arithmetic is that validity is decidable. Hence, given a state formula $f \in SF$ and a program state s we can decide if $s \models f$ by substituting the values of program variables in state s to corresponding open variables in formula f and using a Presburger decision procedure (this is equivalent to checking if $s \wedge f$ is satisfiable).

In general, the worst-case time bound for determining validity in Presburger arithmetic is prohibitive, with a deterministic upper bound of $2^{2^{2^{pn}}}$ (for some constant $p > 1$) [26], and a nondeterministic lower bound of $2^{2^{cn}}$ (for some constant $c > 0$) [17], where n denotes the length of the formula. Yet we have found that the Omega library [21, 28] is quite efficient at solving the problems that arise in our analysis, which typically possess a small number of constraints, and do not contain multiple levels of alternating quantifiers. The Omega library uses extensions of Fourier variable elimination to solve integer programming problems, along with a set of transformation functions and heuristics to help convert real-valued approximations into discrete-valued solutions.

Temporal Properties. We use the temporal logic called Computation Tree Logic (CTL) [8] to specify properties of programs. Four CTL operators form the basis of our logic: quantified-next-state operators $\exists\bigcirc$ and $\forall\bigcirc$, and quantified-until operators $\exists\mathcal{U}$ and $\forall\mathcal{U}$. Thus, the logic we use to reason about a program is generated over the set

$$\{ \ f \in SF \ , \ \exists\bigcirc \ , \ \forall\bigcirc \ , \ \exists\mathcal{U} \ , \ \forall\mathcal{U} \ , \ \wedge \ , \ \vee \ , \ \neg \ \}.$$

As usual, quantified-eventuality ($\exists\Diamond$ and $\forall\Diamond$) and quantified-invariant ($\exists\Box$ and $\forall\Box$) operators can be represented as follows:

$$\begin{array}{lcl@{\qquad\qquad}lcl} \exists\Diamond f & \equiv & \mathsf{True} \ \exists\mathcal{U} \ f & \exists\Box f & \equiv & \neg(\mathsf{True} \ \forall\mathcal{U} \ \neg f) \\ \forall\Diamond f & \equiv & \mathsf{True} \ \forall\mathcal{U} \ f & \forall\Box f & \equiv & \neg(\mathsf{True} \ \exists\mathcal{U} \ f) \end{array}$$

We define the semantics of our CTL temporal operators on the paths of a program's transition system, $M = (S, I, X, L)$. A path $(s_0, s_1, s_2, \ldots)$ is a finite or infinite sequence of states, such that for each successive pair of states $(s_i, s_{i+1}) \in X$. Unlike Clarke *et al.* [8], we do not require the

$s \models f$	iff	$L(s, f) = \mathsf{True}$, where $f \in SF$
$s \models \neg f$	iff	$s \not\models f$
$s \models f \wedge g$	iff	$s \models f$ and $s \models g$
$s \models f \vee g$	iff	$s \models f$ or $s \models g$
$s_0 \models \exists \bigcirc f$	iff	for some maximal path $(s_0, s_1, s_2, \ldots)$, with length ≥ 2, $s_1 \models f$
$s_0 \models \forall \bigcirc f$	iff	for all maximal paths $(s_0, s_1, s_2, \ldots)$, with length ≥ 2, $s_1 \models f$
$s_0 \models f \ \exists\mathcal{U}\ g$	iff	for some maximal path $(s_0, s_1, s_2, \ldots)$, there exists an i, $s_i \models g$, and for all $j < i$, $s_j \models f$.
$s_0 \models f \ \forall\mathcal{U}\ g$	iff	for all maximal paths $(s_0, s_1, s_2, \ldots)$, there exists an i, $s_i \models g$, and for all $j < i$, $s_j \models f$.

Table 1: Semantics of our temporal logic.

transition relation X to be total. Rather, the semantics is defined using maximal paths [4] (as opposed to infinite paths). A maximal path is one which is either infinite, or ends with a state that has no successors. The semantics of the temporal operators can then be defined on a program's transition system $M = (S, I, X, L)$, as shown in Table 1.

If all the initial states of a program satisfy a temporal property, then we say that the program itself satisfies the temporal property. Formally, given a temporal formula f and a transition system $M = (S, I, X, L)$, $M \models f$ only if $\forall s \in I \ : \ s \models f$.

Based on the temporal logic defined above, we can specify the properties of the unbounded-buffer program as follows:

- (UB1) $\forall\Box(p = c + q_1 + q_2)$: The total number of items produced is equal to the number of items consumed, plus the number of items sitting in the two buffers.
- (UB2) $\forall\Box((pc = \mathit{Idle} \ \wedge \ q_1 + q_2 = i) \rightarrow \forall \bigcirc (q_1 + q_2 \leq i))$: If the sender is idle, the number of items in the buffers monotonically decreases.
- (UB3) $\forall\Box(p \geq c)$: The number of items consumed never exceeds the number produced.

Note that the variable i in (UB2) is not a program variable; rather, it is an open integer variable. This points out one of the strengths of our approach – since i can be treated as a symbolic constant within a temporal expression. The interpretation is that i is bound by a universal quantifier (and our Presburger solver treats it as such).

4 Symbolic Representations

Presburger formulas – and their corresponding set-theoretic interpretations – give us a convenient, compact way to symbolically encode large sets of program states and transitions. For our purposes, the benefit of the Presburger encoding is often realized via the arithmetic inequality operators – which we use to implicitly describe large, nontrivial portions of a program's state space. For example, consider the following formula:

$$p - c \leq q_1 + q_2 \leq p \ \wedge \ p, c, q_1, q_2 \geq 0$$

In geometric terms, the constraints represent all points in an unbounded, 4-dimensional polytope. Yet in terms of our example, the shape corresponds to all of the program's reachable states (minus the program-counter).

Similar gains are realized for transitions. Recall that events are described in terms of affine constraints. (This prevents us from using multiplication in a single event, and ensures that single-step image computations are decidable.) Hence, for a given event e, the transition relation of event e, X_e, is representable as a Presburger formula. So using $|E|$ Presburger formulas, one for each event, we can symbolically encode the transition relation X as

$$X \equiv \bigvee_{e \in E} X_e.$$

The fundamental challenge in the Presburger formula encoding is to keep the sizes of the formulas small during the fixpoint computations. Our symbolic manipulator stores Presburger formulas in a disjunctive form where each disjunct corresponds to a convex region in the program's state space. Since each fixpoint iteration is essentially a pre- or post-condition computation, the number of convex regions may increase very quickly in the presence of if-then-else branches and loops.

Given a Presburger formula in a disjunctive form, our minimization procedures try to merge the disjuncts (i.e., convex regions) to reduce the size of the Presburger representation. Assume that we represent each fixpoint iterate using one Presburger formula. After a couple of fixpoint iterations such a representation would generate a Presburger formula with a large number of convex regions. Trying to merge each pair of convex regions one by one would be computationally very expensive. Instead, we use partitioning heuristics. We partition the state space of the program so that the states with similar properties are placed to the same partition class. Then, we represent each fixpoint iterate using one Presburger formula per partition class. This reduces the complexity of the minimization procedures by segregating convex regions which are unlikely to be merged.

We also use approximation techniques to limit the growth of fixpoint iterates. Since the temporal properties we analyze are undecidable, the fixpoint iterations are not guaranteed the converge. Using conservative approximation techniques, we increase the convergence rate of the fixpoint computations. Partitioning heuristics can increase the precision of these approximation techniques. For example one approximation technique could be to merge two convex regions approximately using an upper or a lower bound. Such a technique is more likely to succeed if the merged regions contain states with similar characteristics.

Below we describe our partitioning heuristics. First we describe transition relation partitioning which enables us to compute fixpoint iterations incrementally using one partition class at a time. Then we present our state-space partitioning strategies.

4.1 Transition Relation Partitioning

The most obvious partitioning of the transition relation, X, comes immediately from the event syntax. That is, we can simply perform all transition computations using one event at a time, akin to the way a program's control-points are used in data flow analysis. However, when events contain multiple disjuncts (e.g., from if-then-else constructs), this method proves insufficient for our purposes – since it still generates too many constraints when we carry out automated analysis. In these cases we require a finer-grained technique.

DNF Decomposition. Given two programs $C_1 = (V, I, E_1)$ and $C_2 = (V, I, E_2)$, with the same variables and initial states, assume the following equivalence holds:

$$\bigvee_{e \in E_1} X_e \equiv \bigvee_{e \in E_2} X_e$$

Then C_1 and C_2 are semantically equivalent, since they satisfy exactly the same set of temporal formulas. However, due to their structural differences (and to the methods used in model-checking), one program may be significantly more computationally expensive to analyze than the other. Hence, it often makes sense to transform E_1 into some type of normal-form E_2 – especially when the normal-form has, on average, demonstrated more efficient analysis results.

Such is the case for *disjunctive normal form* (DNF), i.e., where

$$X \equiv \bigvee_{e \in E} X_e, \qquad X_e \equiv \bigwedge_i c_i^e$$

and where each c_i^e is a single affine constraint over primed and unprimed program variables in V. I.e., each X_e corresponds to a convex polytope in $S \times S$.

Clearly, any transition relation X can be so represented – it is simply a matter of converting X into DNF, and then considering each disjunct as a separate event. For example, Figure 3 shows the DNF decomposition of our running program from Figure 2, where for the sake of conciseness, we do not differentiate between an event's "enabled part" and its "action part" (since this is given implicitly by the primed and unprimed variables). Note that the transformation simply split the separate disjuncts from the original events e_S and e_R, and renamed them as separate events.

4.2 State Space Partitioning

Let P be a partitioning of a program's state-space S, where

$$P = \{S_1, S_2, \ldots, S_p\}, \qquad S \equiv \bigvee_{i=1}^{p} S_i, \qquad i \neq j \Rightarrow \; S_i \wedge S_j \equiv \emptyset.$$

$e_{IS} : pc = Idle \ \wedge \ pc' = Send$
$e_{S1} : pc = Send \ \wedge \ p' = p + 1 \ \wedge \ q_1' = q_1 + 1$
$e_{S2} : pc = Send \ \wedge \ p' = p + 1 \ \wedge \ q_2' = q_2 + 1$
$e_{SI} : pc = Send \ \wedge \ pc' = Idle$
$e_{R1} : q_1 > 0 \ \wedge \ q_1' = q_1 - 1 \ \wedge \ c' = c + 1$
$e_{R2} : q_2 > 0 \ \wedge \ q_2' = q_2 - 1 \ \wedge \ c' = c + 1$

Figure 3: DNF Event-Decomposition.

Then if $Q \subseteq S$ is a subset of program states, we can decompose Q via our partitioning P of S:

$$Q \equiv \bigvee_{i=1}^{p} q_i, \quad \text{where} \quad q_i \equiv Q \wedge S_i.$$

This technique will only prove worthwhile where each S_i unites states with common characteristics (that is, when key formulas are true either for all the states in S_i or none of the states in S_i), and when P distinguishes between large regions of S possessing different characteristics.

Below we present two techniques which can often create such a partitioning, and which are two of the "default options" in our model-checker.

Control-Point Partitioning. Given a program $C = (V, I, E)$, assume we partition the variables into two classes:

$$V = V_1 \cup V_2 \quad \text{s.t.} \quad V_1 \cap V_2 = \emptyset.$$

The valuations for V_1 (or V_2) induce a natural partitioning of S. Letting $V_1 = \{v_{11}, \ldots, v_{1m}\}$, equivalence classes are defined simply as:

$$S_{(x_{11}, \ldots, x_{1m})} \ \equiv \ \bigwedge_{j=1}^{m} v_{1j} = x_{1j} \quad \text{s.t.} \quad x_{1j} \in \mathbf{domain}(v_{1j}).$$

Of course, if V_1 contains many variables, or if their domains are large, we may end up with a huge number of classes; hence the partition variables have to be chosen with care.

Fortunately, many programs yield a natural choice for V_1 – the control points – the number of which are usually far fewer than state valuations. To enable this type of partitioning, our event language makes a syntactic distinction between control and data variables (while semantically, they are considered the same). When our preprocessor translates event-action language code into events, the control variables are isolated as such, which then allows a default partitioning according to their values.

When applied to the program in Figure 2, this strategy yields $V_1 = \{pc\}$ and the following two partition classes (shown pictorially in Figure 4):

$$S_{Idle} \equiv pc = Idle \qquad S_{Send} \equiv pc = Send$$



Figure 4: Control-Point Partitioning.



Figure 5: Event-Domain Partitioning.

and so, our partitioning is $P = \{S_{Idle}, S_{Send}\}$. Now consider a formula $Q \equiv p > c$, representing all states in which more items were produced than consumed. The formula is partitioned as $P_Q = \{Q_{Idle}, Q_{Send}\}$, where,

$$Q_{Idle} \equiv pc = Idle \wedge p > c \qquad Q_{Send} \equiv pc = Send \wedge p > c$$

with $Q \equiv Q_{Idle} \vee Q_{Send}$.

Event-Domain Partitioning. The method above can also be generalized to the "implicit control points" inherent in the raw events themselves. In essence, an event's natural control point is just its enabling condition. And, using the enabling conditions as partitioning criterion can yield a much finer-grained decomposition. (This is obviously true when no control variables are isolated in a program.) In this partitioning, each class denotes a region of S in which a specific set of events are enabled to fire. So, given $C = (V, I, E)$, we define its event-domain partitioning P as:

$$P = \{ \ S_i \mid \forall e \in E \ : \ (S_i \wedge \mathbf{domain}(e)) \equiv S_i \ \vee \ (S_i \wedge \neg\mathbf{domain}(e)) \equiv S_i \ \}$$

While this technique yields potentially $2^{|E|}$ partition classes, note that most of these partition classes will probably be empty. The reason is that most of the events will typically have mutually exclusive enabling conditions.

SYMBOLIC OMEGA OPERATIONS		
$F \wedge G$	:	symbolic intersection
$F \vee G$	:	symbolic union
$\neg F$	:	symbolic complement
F^{-1}	:	symbolic inverse of relation F
$F[G]$	:	restrict domain of relation F to constraint G and return the range of the result
$\mathbf{hull}(F)$	:	convex hull of F

Figure 6: Symbolic Omega Functions.

This is certainly the case when we apply the technique to our running example from Figure 2. Event-domain partitioning yields only 4 feasible partition classes (shown pictorially in Figure 5), which is significantly less than $2^{|E|} = 2^4 = 16$. These 4 partition classes are as follows (where each partition class is indexed by the events enabled in the class):

$$\begin{array}{lcllcl} S_{(IS,R)} & \equiv & pc = Idle \wedge (q_1 > 0 \vee q_2 > 0) & S_{(S,SI)} & \equiv & pc = Send \wedge q_1 = 0 \wedge q_2 = 0 \\ S_{(S,SI,R)} & \equiv & pc = Send \wedge (q_1 > 0 \vee q_2 > 0) & S_{(IS)} & \equiv & pc = Idle \wedge q_1 = 0 \wedge q_2 = 0 \end{array}$$

Note that if we have had used the DNF event partitioning first (from Figure 3), we would have produced a finer partitioning with more classes.

5 Symbolic Model-Checker

After generating our symbolic representations in terms of Presburger formulas, we use the Omega library [21] to help *symbolically* compute the truth sets for the temporal properties at hand. The Omega library includes a large collection of object classes to efficiently manipulate Presburger formulas; to date it has mainly been used in high-performance compilers, specifically for dependence analysis, program transformations, and detecting redundant synchronization [22, 28, 29]. The particular Omega functions we use are shown in Figure 6. These functions take symbolic representations of sets or relations as inputs (i.e., a Presburger formula representing a set or a relation), and return the symbolic form of a set or a relation as output.

To symbolically compute the temporal operators, we define a function $\mathbf{pre} : 2^S \to 2^S$, called the *precondition function*, which, given a set of states, returns all the states that can reach this set in one step (i.e. after execution of a single event):

$$\mathbf{pre}(Q) \stackrel{\text{def}}{=} \{ s \mid \exists s' : s' \in Q \wedge (s, s') \in X \}.$$

Using the Omega operator in Figure 6 we have $\mathbf{pre}(Q) \equiv X^{-1}[Q]$. Moreover, we can symbolically compute **pre** with respect to our program's partitioning, and maintain a formula for each partition class, as follows:

$$\mathbf{pre}(Q) \;\equiv\; \mathbf{pre}(\bigvee_{S_i \in P} (Q \;\wedge\; S_i)) \;\equiv\; \bigvee_{S_i \in P} \mathbf{pre}(Q \;\wedge\; S_i) \;\equiv\; \bigvee_{S_i \in P, e \in E} X_e^{-1}[Q \wedge S_i]$$

By performing this computation individually for each partition class, we exploit the fact that many formulas inherently involve only small parts of the program's state space. For example, consider the unbounded buffer example – and specifically, the states where producer is *Idle* and buffers are empty:

$$Q \equiv pc = Idle \wedge q_1 = 0 \wedge q_2 = 0.$$

Using control point partitioning, we have

$$\begin{aligned}\mathbf{pre}(Q) \;&\equiv\; \bigvee_{e \in \{e_r, e_{s2}\}} X_e^{-1}[Q \;\wedge\; S_{Idle}] \\ &\equiv\; pc = Idle \wedge (q_1 = 1 \wedge q_2 = 0 \vee q_2 = 1 \wedge q_1 = 0) \vee \; pc = Send \wedge q_1 = 0 \wedge q_2 = 0\end{aligned}$$

Now, given a symbolic representation for a set f, we can symbolically compute $\exists \bigcirc f$ and $\forall \bigcirc f$ using **pre**, as follows:

$$\exists \bigcirc f \equiv \mathbf{pre}(f) \qquad \text{and} \qquad \forall \bigcirc f \equiv \neg\mathbf{pre}(\neg f).$$

As for $\exists\mathcal{U}$ and $\forall\mathcal{U}$, consider the following functionals:

$$\mathcal{F}_{f_1 \exists\mathcal{U} f_2} \equiv \lambda y \;.\; f_2 \vee (f_1 \wedge \exists \bigcirc y) \qquad \text{and} \qquad \mathcal{F}_{f_1 \forall\mathcal{U} f_2} \equiv \lambda y \;.\; f_2 \vee (f_1 \wedge \forall \bigcirc y \wedge \exists \bigcirc y).$$

The least fixpoints of $\mathcal{F}_{f_1 \exists\mathcal{U} f_2}$ and $\mathcal{F}_{f_1 \forall\mathcal{U} f_2}$ are equal to $f_1 \; \exists\mathcal{U} \; f_2$ and $f_1 \; \forall\mathcal{U} \; f_2$, respectively. We have the following result from elementary lattice theory:

Property 1 *For all transition systems, for all $n \in \mathcal{Z}$,*

$$\begin{aligned}f_1 \; \exists\mathcal{U} \; f_2 \;&\supseteq\; \bigvee_{i=0}^{n} (\lambda y \;.\; f_2 \vee (f_1 \wedge \exists \bigcirc y))^i(\mathsf{False}) \equiv \bigvee_{i=0}^{n} \mathcal{F}^i_{f_1 \exists\mathcal{U} f_2}(\mathsf{False}) \\ f_1 \; \forall\mathcal{U} \; f_2 \;&\supseteq\; \bigvee_{i=0}^{n} (\lambda y \;.\; f_2 \vee (f_1 \wedge \forall \bigcirc y \wedge \exists \bigcirc y))^i(\mathsf{False}) \equiv \bigvee_{i=0}^{n} \mathcal{F}^i_{f_1 \forall\mathcal{U} f_2}(\mathsf{False})\end{aligned}$$

where, given a functional $\mathcal{F}$, $\mathcal{F}^i(f)$ is defined as:

$$\mathcal{F}^i(f) \stackrel{\text{def}}{=} \underbrace{\mathcal{F}(\mathcal{F}(\ldots \mathcal{F}(}_{i \text{ times}} f)) \ldots).$$

By the monotonicity of $\mathcal{F}_{f_1 \exists\mathcal{U} f_2}$ and $\mathcal{F}_{f_1 \forall\mathcal{U} f_2}$, we get

$$\bigvee_{i=0}^{n} \mathcal{F}^i_{f_1 \exists\mathcal{U} f_2}(\emptyset) \equiv \mathcal{F}^n_{f_1 \exists\mathcal{U} f_2}(\emptyset) \qquad \text{and} \qquad \bigvee_{i=0}^{n} \mathcal{F}^i_{f_1 \forall\mathcal{U} f_2}(\emptyset) \equiv \mathcal{F}^n_{f_1 \forall\mathcal{U} f_2}(\emptyset).$$

PROCEDURE CHECK(f)		
CASE		
$f \in SF$	:	RETURN(f)
$f = \neg f_1$	:	RETURN($\neg f_1$)
$f = f_1 \wedge f_2$	:	RETURN($f_1 \wedge f_2$)
$f = f_1 \vee f_2$	:	RETURN($f_1 \vee f_2$)
$f = \exists \bigcirc f_1$	:	RETURN($\mathbf{pre}(f_1)$)
$f = \forall \bigcirc f_1$	:	RETURN($\neg\mathbf{pre}(\neg f_1)$)
$f = f_1 \ \exists\mathcal{U} \ f_2$	:	$Q_0 \equiv f_2 \quad Q_{i+1} \equiv Q_i \vee (f_1 \wedge \mathbf{pre}(Q_i))$
		RETURN(Q_n) when $Q_n \equiv Q_{n+1}$
$f = f_1 \ \forall\mathcal{U} \ f_2$	:	$Q_0 \equiv f_2 \quad Q_{i+1} \equiv Q_i \vee (f_1 \wedge \mathbf{pre}(Q_i) \wedge (\neg\mathbf{pre}(\neg Q_i)))$
		RETURN(Q_n) when $Q_n \equiv Q_{n+1}$

Figure 7: Symbolic Model Checker.

Then using Property 1, it can be shown that every element in the sequence $\mathsf{False} \equiv \emptyset$, $\mathcal{F}_{f_1\exists\mathcal{U}f_2}(\emptyset)$, $\mathcal{F}^2_{f_1\exists\mathcal{U}f_2}(\emptyset)$, $\mathcal{F}^3_{f_1\exists\mathcal{U}f_2}(\emptyset), \ldots$, is a subset of the least fixpoint of $\mathcal{F}_{f_1\exists\mathcal{U}f_2}$; similarly, every element in the sequence $\mathsf{False} \equiv \emptyset$, $\mathcal{F}_{f_1\forall\mathcal{U}f_2}(\emptyset)$, $\mathcal{F}^2_{f_1\forall\mathcal{U}f_2}(\emptyset)$, $\mathcal{F}^3_{f_1\forall\mathcal{U}f_2}(\emptyset), \ldots$, is a subset of the least fixpoint of $\mathcal{F}_{f_1\forall\mathcal{U}f_2}$. Since $\mathcal{F}_{f_1\exists\mathcal{U}f_2}$ and $\mathcal{F}_{f_1\forall\mathcal{U}f_2}$ are both monotonic, and since we start the sequence with $\emptyset$, these sequences are non-decreasing. When these monotonically increasing sequences reach a fixpoint, we know that it is the least fixpoint [25].

These methods lead directly to the model checking procedure shown in Figure 7 (subformulas are computed recursively). Given a program and a temporal logic formula, the model checker will (attempt to) symbolically compute the set of program states that satisfy the input formula – and the procedure will yield an exact answer if it converges. Note that this procedure is a partial-function, i.e., it is not guaranteed to terminate.

We analyzed the running example given in Figure 2 using control point partitioning and the exact model checking procedure given in Figure 7. Recall that one of the requirements for this program was $\forall\Box(p = c + q_1 + q_2)$ which is equivalent to: $\neg(\mathsf{True}\ \exists\mathcal{U}\ (p \neq c + q_1 + q_2))$ or $\neg\exists\Diamond(p \neq c+q_1+q_2)$. (Although our basic temporal operators are $\exists\mathcal{U}$ and AU, when possible we will use their $\exists\Diamond$ and $\forall\Diamond$ equivalents for clarity of presentation). To compute the least fixpoint $\exists\Diamond(p \neq c+q_1+q_2)$, the model checker initialized the first iterate to $Q_0 \equiv p \neq c + q_1 + q_2$. The fixpoint computation trivially converged after one iteration to Q, where Q is partitioned as follows:

$$Q_{Idle} \equiv pc = Idle \wedge p \neq c + q_1 + q_2 \qquad\qquad Q_{Send} \equiv pc = Send \wedge p \neq c + q_1 + q_2$$

Our top-level formula is $\neg\exists\Diamond(p \neq c + q_1 + q_2)$; hence, the model checker computes $\neg Q$. This yields the set of states which can never reach a violation of the assertion $p = c + q_1 + q_2$. Since the initial condition for the program is $I \equiv p = 0 \wedge c = 0 \wedge q_1 = 0 \wedge q_2 = 0$, it is easy to see that $I \subseteq \neg Q$ (i.e., all of the initial states satisfy the safety property). Hence, the model checker reports that the property is proved (for a total computation time of 0.88 seconds on a Sun SPARCstation 5). The exact model checker also successfully proved the property $\forall\Box((pcs = Idle \wedge q_1 + q_2 = i) \rightarrow \forall \bigcirc (q_1 + q_2 \leq i))$ in 0.77 seconds.

6 Approximation Techniques

Since we have a Turing-computable language, our exact model-checker in Figure 7 may keep iterating forever without reaching a fixpoint. Thus, we also need a conservative approximation method, which will always converge. We define a conservative analyzer as one which always terminates and never yields a spurious result, but may not be able to produce a definite answer in certain cases.

Indeed, our exact analyzer diverged when we fed the unbounded-buffer program, along with its other requirement: $\forall\Box(p \geq c)$. When the exact analyzer went to work on this property, it attempted to symbolically enumerate ways that p could be less than c. Since c is unbounded, this method failed to converge. But as we show in the sequel, the same property was easily proved using a conservative approximation.

6.1 Conservative Analysis

If we cannot directly compute a property f for a program C, the next best thing is to generate a lower-bound for f, denoted f^-, such that $f^- \subseteq f$. Then if we determine that $I \subseteq f^-$, we have also achieved our objective – that $I \subseteq f$, (i.e., we proved that $C \models f$). However, if $I \not\subseteq f^-$, we cannot conclude anything because it can be a *false negative*. In that case we can compute a lower bound for the negated property: $(\neg f)^-$. If we can find a state s such that $s \in I \cap (\neg f)^-$, then we can generate a counter example which would be a *true negative*. If both cases fail, i.e., both $I \not\subseteq f^-$ and $I \cap (\neg f)^- \equiv \emptyset$, then the analyzer can not report a definite answer.

Since we seek to carry out our analysis in a recursive manner (as in the exact analyzer in Figure 7), we have to compute an approximation to a formula by first computing approximations for its subformulas. Hence, to compute a lower bound to a property like $g \equiv \neg h$, we first need to compute an *upper* approximation h^+ for the subformula h, and then let $g^- \equiv S - h^+$. This follows directly from set theory, since $(\neg f)^- \equiv \neg(f^+)$ and $(\neg f)^+ \equiv \neg(f^-)$. Thus, we need algorithms to compute both lower and upper bounds of temporal formulas.

When analyzing a negation-free formula, the compositionality of an approximation follows directly from the fact that all operators other than "$\neg$" are monotonic. This means that any lower/upper approximation for a negation free formula can be computed using the corresponding lower/upper approximation for its subformulas. As for handling arbitrary levels of negation, we can easily generalize the above mentioned method for outermost negation operators. That is, to approximate a temporal formula f, the following procedure determines which of f's subformulas require an upper bound, and which require a lower bound.

1. Mark the root of the parse tree for formula f with a minus sign ("$-$") if a lower bound is desired, and with a plus sign ("+") if an upper bound is desired.
2. Using a preorder tree traversal, visit each node in the tree, mark each node with the mark of its parent, unless its parent is a $\neg$ operator. In that case, mark the node with the opposite bound.

6.2 Computing Upper Bounds with Widening Technique

When the algorithms in Figure 7 attempt to compute fixpoints for $\exists\mathcal{U}$ and $\forall\mathcal{U}$, they may generate sequences of increasing lower bounds which never converge. From elementary fixpoint theory, we know that a least fixpoint exists – but it may simply not be computable. Hence, our job is to accelerate the computation, and "leap-frog" over multiple members of the chain – perhaps at the risk of over-shooting the exact least fixpoint. As long as the result is larger than the exact fixpoint, we have an upper approximation.

The way we go about this is as follows. If the exact iteration sequence is $Q_0, Q_1, Q_2, \ldots$, then we find a *majorizing* sequence $\hat{Q}_0, \hat{Q}_1, \hat{Q}_2, \ldots$, such that (1) for each i, $Q_i \subseteq \hat{Q}_i$, and (2) the $\hat{Q}_i$ sequence reaches a fixpoint after finitely many iterates. Thus the fixpoint of the $\hat{Q}_i$'s is an upper approximation to the least fixpoint of the Q_i's.

To generate the $\hat{Q}_i$'s, we currently adopt a method developed by Cousot and Cousot, within the framework of abstract interpretation [12]. That is, we define an operator called widening, or "$\bigtriangledown$", which majorizes the union computation as follows: For any pair of sets P, P', $P \vee P' \subseteq P \bigtriangledown P'$. Using a suitable widening operator, we can compute an upper bound for $f_1\ \exists\mathcal{U}\ f_2$ as:

$$\begin{aligned}
\hat{Q}_i &\equiv \begin{cases} Q_i & \text{if } \ 0 \le i \le s \\ \hat{Q}_{i-1} \bigtriangledown (\hat{Q}_{i-1} \vee (f_1 \ \wedge \ \mathbf{pre}(\hat{Q}_{i-1}))) & \text{if } \ i > s \end{cases} \\
(f_1\ \exists\mathcal{U}\ f_2)^+ &\equiv \hat{Q}_n \text{ when } \hat{Q}_n \equiv \hat{Q}_{n+1}
\end{aligned}$$

where $Q_0, Q_1, Q_2, \ldots$, is the sequence generated by the procedure for $f_1\ \exists\mathcal{U}\ f_2$ in Figure 7, and s is the *seed* of the widening sequence. From the monotonicity of the **pre** operator, one can easily show by induction that iterates of this sequence do indeed majorize the Q_i's computed in Figure 7. And when this sequence terminates, the final iterate is an upper bound for $f_1\ \exists\mathcal{U}\ f_2$. For the $f_1\ \forall\mathcal{U}\ f_2$ we can generate a similar majorizing sequence as:

$$\begin{aligned}
\hat{Q}_i &\equiv \begin{cases} Q_i & \text{if } \ 0 \le i \le s \\ \hat{Q}_{i-1} \bigtriangledown (\hat{Q}_{i-1} \vee (f_1 \ \wedge \ \mathbf{pre}(\hat{Q}_{i-1}) \wedge (\neg\mathbf{pre}(\neg\hat{Q}_{i-1})))) & \text{if } \ i > s \end{cases} \\
(f_1\ \forall\mathcal{U}\ f_2)^+ &\equiv \hat{Q}_n \text{ when } \hat{Q}_n \equiv \hat{Q}_{n+1}
\end{aligned}$$