Guaranteeing Safety in the Presence of Moving Obstacles

Robert C. Kohout

ABSTRACT

Path planning is a fundamental problem in robotics research. Whether the robot is a manipulator arm in a factory floor, an unmanned all-terrain vehicle, a flying drone, or a household assistant serving coffee, the motions of the robot must be planned and executed in such a way that the robot can accomplish its goals. Motion planning must take into account the robot's inherent abilities to move and maneuver, its speed, and all of the various constraints imposed upon these abilities by the environment in which the robot is situated. Many real-world application domains are dynamic, in the sense that the plan-relevant parameters in the environment evolve over time. In such cases, motion planning must also take into account the time that it takes to plan. A perfect plan is useless if it cannot be produced in time to execute it in a changing world.

This technical report focuses upon the problem of avoiding moving obstacles in a 2-dimensional environment. Specifically, it addresses the problem of guaranteeing that a robot will never be hit by an obstacle in the environment. It establishes conditions for guaranteeing that a safety-preserving path will always exist in the most commonly studied problem in moving obstacle avoidance, known as the Asteroids Avoidance Problem. These results are then extended to less restricted, more realistic variants of the problem, including the important case where the locations and trajectories are only made known to the planning algorithm at runtime.

Once these conditions are established, they are used to develop an incremental algorithm that can solve the restricted Asteroids problem in low-order polynomial time. This algorithm takes its own observed worst-case running time into account, completes in a fraction of a second, and has been used to control Dodger, a simulated robot that avoids moving obstacles in hard real time. In over ten machine-weeks of testing, involving well over a million obstacles generated in a variety of ways, Dodger has not been hit by a single obstacle.

The research described in this report was conducted by the author in partial fulfillment of the doctoral degree requirements at the University of Maryland, College Park, under the direction of Prof.James A. Hendler. This research was supported in part by grants from the ARPA/Rome Laboratory Planning Initiative (F30602-93-C-0039), the ARPA I3 Initiative (N00014-94-10907), NSF (IRI-9306580), ONR (N00014-J-91-1451), AFOSR (F49620-93-1-0065), and ARPA contract DAST-95-C0037. Dr. Hendler is also affiliated with the UM Institute for Systems Research (NSF Grant NSF EEC 94-02384).

Chapter 1

Introduction

Many real-world applications require both intelligence and timeliness. Factory automation systems need to understand and manipulate complex operating environments, and quickly adjust when orders change, machines break or anticipated supplies are not delivered. Vehicle dispatching systems need to decide which vehicles to send where, and when, while adjusting to changing traffic conditions and customer demands. Military command and control systems need to acquire, integrate, and summarize huge amounts of complex, conflicting and often unreliable data in time to decide what actions should be taken on the battlefield. Highway vehicles must operate at high speeds in rapidly changing environments, and negotiate roadways fraught with hazards. In most cases, the bulk of information processing in each of these systems is currently done by human beings. In each case, people have long sought to automate large portions of the overall task. If these goals are ever to be achieved, the often conflicting requirements for intelligence and timeliness must be addressed.

This report brings together two major disciplines of Computer Science: Artificial Intelligence (AI), and Real-Time Computing. These two research areas conflict fundamentally. Real-Time Computing focuses upon the design of systems that perform with predictable precision, so that correct behaviors can be guaranteed. This sort of predictability is antithetical to the wide range of behavior that characterizes intelligence, and the classical methods of AI reflect this. Intuitively, intelligence involves deliberation, and deliberation takes time. More to the point, like people, a modern AI system will solve simple problems quickly, but more difficult problems take more time. It is possible to develop AI systems that return **some** result within a given time bound, but with very few exceptions, the quality of this result cannot be assured. This report takes a problem that has traditionally been addressed by conventional AI search techniques, and finds a solution to this problem that is **provably** adequate, both with respect to quality and timeliness.

1.1 Motivation

To be autonomous, a mobile robot must be able to plan its motions through time and space. Thus motion planning is a fundamental and well studied problem in mobile robotics. Whether the machine is a wheeled robot maneuvering through the corridors of a University, a manipulator arm on a factory floor, an unmanned vehicle negotiating rough outdoor terrain, or a deep space probe, billions of miles from earth, the problem of determining how to get from one place to another occurs over and over again in robotic applications.

Each application domain has its own unique geometry, and each robot has its own set of sensors and effectors. As a result, the field of motion planning is broad and many-faceted. This report focuses upon a particular kind of motion planning, namely, the problems associated with avoiding moving obstacles while maneuvering in a plane. Such problems arise naturally in a variety of real-world applications, and consequently, there has been considerable research in this area. The main contribution that this report makes to the existing body of research is its examination of the issues involved in **guaranteeing** obstacle avoidance in such domains.

It is easy to see why such guarantees are desirable. In most applications, getting hit by a car, a forklift, or other another robots, is a very costly and undesirable event. In addition, an important class of control systems, known as "mission-critical" real-time systems, is further complicated by the potential for catastrophic failure if the system does not produce acceptable behavior within strict deadlines. This makes it imperative that system operation can be proven correct before deployment. In particular, it is not sufficient that response times be "fast." When the cost of failure may be catastrophic, it is essential that we can **prove** that response time is "fast enough." Because of the potentially high cost of inadequate timeliness, **temporal adequacy** must be a fundamental component of the design and analysis of mission-critical systems. If mobile robots are ever going to be deployed in mission-critical applications, we need some way to guarantee that they will always be able to find and execute safety-preserving paths.

It also easy to see that, in practice, absolute guarantees of correct **system** behavior cannot be made. Sensors and effectors are never completely accurate, and software models will never completely capture all of the potentially relevant details of the world. The best that system designers can reasonably hope for is to minimize the overall possibility of failure. However, even though hardware and software are inherently limited, it is still useful to determine the theoretical limits and possibilities within a domain. In fact, if one desires to engineer a high-reliability system, it is necessary to first establish the theoretical bounds on system performance, and then endeavor to minimize the deviations from the theoretical optima in a realized system.

1.2 Contributions

The Asteroids Avoidance Problem can be stated as follows:

> Given a robot, at initial location R, that is capable of instantaneous, unbounded acceleration, up to some maximum speed V_r, and a set of moving obstacles $O_1, O_2, \ldots O_n$, that move at known, constant linear velocities, find a "safety-preserving" path that the robot can travel to avoid being hit by any of the obstacles.

This is the best known and most often studied problem in moving obstacle avoidance. This report establishes the theoretical conditions under which it is possible to guarantee safety in the Asteroids Problem. It then examines the ways in which the assumptions of the problem can be relaxed, while still guaranteeing avoidance, and establishes conditions for guaranteeing that a robot can always make progress towards its goals, while still avoiding all moving obstacles.

If a system has deadlines which absolutely must be met in order to assure system safety, the deadlines are known as "hard" deadlines, and a system designed to ensure that all such hard deadlines can be met is a "hard real time" system. In a hard real time system, overall system utility can go to zero when a deadline is missed. If system utility diminishes, but will still have some positive value when a deadline is missed, the deadline is said to be "soft." In order to ensure that all of the required resources are always available to a hard real time system, shared resources are typically **scheduled** , in such a way that even in the worst case, all of the required deadlines can be met. This generally means that some sort of calendar is created that maps shared resources to system processes as a function of time.

This work is groundbreaking because it is the first research in moving obstacle avoidance that takes the runtime of the algorithm into account when solving the avoidance problem. In order to guarantee avoidance, it is not enough to expect fast processors and good engineering to suffice to ensure timeliness. The running time of the algorithms must be accounted for in the control strategy that is used to avoid obstacles. To be useful, an avoidance algorithm must produce results before they become obsolete. As an algorithm is running, the world may change, and thus render any ongoing computation invalid. In all dynamic domains, the time required to find a solution is a fundamental part of the problem, but prior to this report this issue had never been addressed in the context of moving obstacle avoidance.

Dodger, a simulated robot that avoids moving obstacles in hard real time, was implemented based upon this report's theoretical results in obstacle avoidance. Dodger demonstrates that, in exactly the subclass of the Asteroids Problem where it is possible to ensure that safety will always exist, it is also possible to design and implement a reactive avoidance strategy that suffices to avoid obstacles in real time. Since its last bug was fixed, Dodger has avoided over a million obstacles in the course of over 60 days of real-time tests, conducted in a variety of different obstacle-generating scenarios, and **has not been hit by a single obstacle.** The algorithm employed by Dodger is complete, in the sense that a safety-preserving path to a goal is always found, and runs in a fraction of a second. This algorithm is $O(N \log N)$ worst-case, but empirical evidence suggests that actual performance is much better than this.

Most of the previous work in moving obstacle avoidance has focused upon a "static" problem. That is, the problem specifics are known to the algorithm when it begins, and they do not change afterwards. An implicit assumption in this approach is that such an algorithm can be easily modified to address the more realistic, "dynamic" case, where aspects of the problem become known to the control system over time, and are subject to change. This report establishes a fundamental difference between the static and dynamic variants of the Asteroids Problem. Necessary and sufficient conditions for guaranteeing safety in the static case are derived in Chapter 3 of this report. The proof of these properties is constructive, and suggests a straightforward algorithm for solving the problem when the requisite conditions are known to hold true. However, this algorithm is **not** sufficient to ensure safety in the dynamic version of the problem, where moving obstacles appear and disappear with the passage of time. While this report establishes sufficient conditions for ensuring obstacle avoidance, it does not show that these conditions are also necessary. In fact, it presents empirical evidence that strongly suggests that they are **not** necessary.

1.3 Brief Outline

This report contains seven additional chapters. Chapter 2 reviews the existing literature in robot motion planning. Chapter 3 develops the theoretical constructs that are required to ensure that a robot will always be able to avoid moving obstacles. Chapter 4 contains the algorithms required to implement these theoretical results in Dodger. Chapter 5 contains a description of a classical AI search algorithm that could be used to solve the static variant of the Asteroids Problem. Chapter 6 describes Dodger, a robot simulation that solves the Asteroids Avoidance problem in real time. Chapter 7 contains the empirical evaluations of Dodger and its algorithms. Chapter 8 summarizes this research effort, and discuss avenues for future work.

1.4 Detailed Outline

Chapter 2 reviews previous work in robot motion planning, including both time-invariant domains, where none of the obstacles change position over time, and time-varying domains, in which obstacles may move. Particular attention is paid to whether the problem is static or dynamic (i.e., whether or not all of the relevant information is known to the planning system at the time it begins to plan a path), and whether the algorithm is **complete**, in the sense that it will always find a solution when a solution exists. This chapter also examines the claims of real-time performance that are often associated with such path-planning systems.

Chapter 3 contains the main theoretical results of this report. I begin by establishing necessary and sufficient conditions for guaranteeing safety in the classical (static) version of the Asteroids Problem, and then I use these results to establish sufficient conditions for guaranteeing safety in the more natural, dynamic version of this problem. Chapter 3 then proceeds to examine ways in which the assumptions and restrictions of the Asteroids problem can be relaxed, while still allowing avoidance to be guaranteed. This chapter ends by establishing conditions for guaranteeing that the robot can always make progress towards its goal.

The proof for necessary and sufficient conditions in the Asteroids problem is constructive, so much of the avoidance algorithm can be derived directly from the proof. Chapter 4 addreses the one major algorithmic question raised by the proof, namely, how to find a "safe haven" location that the robot can move to, in two different way. First is an algorithm for deterministically finding a "safe haven", and then a Monte Carlo technique is also described. This chapter also contains a description of the goal achievement heuristics that are used in the Dodger system.

Chapter 5 contains a detailed description of a search algorithm for solving the static Asteroids Problem. Based upon earlier work, this chapter explicitly addresses many of the issues that had been treated as details in that work. It also develops the techniques and algorithms that are used for ensuring safety in the Dodger system.

Chapter 6 describes Dodger and the Maruti Hard Real-Time Operating System upon which it runs. It describes the particular variant of the Asteroids Problem that Dodger solves, including the various schemes for generating obstacles that were used to test Dodger. Chapter 6 then presents the system architecture, including the ways in which Dodger depends upon the services of Maruti.

In Chapter 7 presents the results of various empirical studies. It begin by presenting some results of the behavior of the complete search algorithm described in Chapter 5, proceeds to the empirical analyses of Dodger, beginning with a study of how Dodger behaves across a variety of obstacle generation strategies and goal achievement heuristics. This Chapter then analyzes both the worst-case and average-case runtime behavior of the avoidance algorithm. This chapter concludes with an empirical investigation of the necessary conditions for guaranteeing safety in the dynamic version of the Asteroids Problem.

Chapter 8 summarizes this report, and concludes with a discussion of possible ways in which this work can be extended in future research.

Chapter 2

Previous Work

2.1 Introduction

Motion planning has been a fundamental component of Robotics research from the time the first mobile robots were constructed in the late 1960's. 65 (65) describes what may be the earliest such robot, and this description includes a discussion of a graph-search algorithm used to determine the shortest collision-free path from the robot's location to a goal position. In the almost 30 years since that time, a large body of research has focused upon the problems associated with determining how to direct a mechanical robot from one location to another, subject to constraints imposed by the application environment and the mechanical constraints of the robot itself.

Broadly speaking, motion planning problems fall into two categories. **Gross motion planning** focuses on problems involving distances much greater than the size of the robot. **Fine motion planning** revolves around the problem of moving an object in a narrow space, where the required accuracy of motion approaches, or even exceeds, the positional accuracy of the robot. This report, and the rest of this chapter, is solely concerned with problems and issues implicit in gross motion planning. Throughout this report, the terms "motion planning" and "path planning" are used interchangeably, to refer to problems associated with planning the gross motions of mobile robots. There are a number of excellent surveys of gross motion planning research, including (39; 54; 82). The reader should refer to these for detailed descriptions of research that falls beyond the scope of this chapter and this report.

Adopting terminology from 39 (39), gross motion planning can be categorized as either **time-invariant** or **time-variant**, according to whether or not the obstacles in the domain can change position over time. This report focuses upon time-variant problems, which can be viewed as a proper superset of time-invariant problems, but I shall review the major results in time-invariant motion planning, since much of it is relevant to the time-variant case. Path-planning problems can also be either **static**, in which all of the obstacle information is known to the planner prior to planning, or **dynamic**, in which information about obstacles becomes known to the planner over time, and after the planning process in initiated. The vast majority of path-planning literature focuses upon the static case, but the vast majority of real-world path-planning applications fall into the dynamic case.

Most time-variant robot application environments are not of a nature which allows all of the relevant information to be known **a priori**, and yet the bulk of research into time-varying path-planning falls into the static category. Such work is based upon a generally unstated assumption, namely, that the time required to compute a solution is irrelevant to the problem. By definition, time-varying domains can change between the time that an algorithm begins, and the time that it finishes. However, this issue is rarely, if ever, addressed by researchers working within this paradigm.

The implicit assumption is that, if static solutions can be developed, then adapting them to more realistic, dynamic solutions will be relatively straightforward. However, as this report shows, there are fundamental differences between the static and the dynamic problems. In static problems, an algorithm has complete information, and any solution it finds to a given problem is guaranteed to suffice, due to the static nature of the domain. In contrast, dynamic problems must take into account not only the events known to have occurred, but also any events that might **possibly** occur. Thus the set of solutions is more constrained in the dynamic case.

Section 3.1.1 (page 15) develops necessary and sufficient conditions for guaranteeing safety in the best known and most commonly studied problem in time-varying path-planning. However, this result does **not** transfer directly to the dynamic case. Section 3.1.2 (page 19) establishes sufficient conditions for the dynamic version of this problem, which are qualitatively different from those in the static problem. The fact that these conditions have not been shown to be necessary does not contradict the contention that the static problem is fundamentally different from the dynamic problem. Even if it does eventually prove to be possible to guarantee safety under the same conditions in both the static and dynamic versions of the problem, it is definitely **not** the case that the algorithms developed in this report to ensure safety in the static version of this problem also suffice in the dynamic case.

2.1.1 Real-Time Motion Planning

There has been significant research in the area of dynamic motion planning. Typically, such studies are associated with the control of actual robots, and so the convenience of the static assumption cannot be adopted. Many of the papers in this area purport to describe real-time algorithms. With only a very few notable exceptions, these real-time claims stem directly from the dynamic nature of the problem. In other words, most work in "real-time path-planning" is more correctly categorized as research in dynamic path planning, since the real-time aspects of the work are confined to the fact that data is gathered "online", after system execution has begun. Such claims are not atypical, and stem generally from the looser definition of real time adopted outside of the real-time systems community. As 32 (32) put it

> A strict definition of real time is that the system guarantees that tasks will receive up to their worst-case runtime and resource requirements, which presumably means that tasks will produce the best possible results (highest quality results). In real-time AI the focus is usually on high-level goal achievement, rather than worst-case requirements. For this reason, often in real-time AI less strict definitions of real time are used. One common (and usually implicit) definition is that the system will statistically (e.g., on average) achieve the required quality value by the required time, but no guarantee is made about any particular task[1].

Inside of the real-time systems community, it is recognized that not all systems are **hard real time** Such systems are constrained by hard deadlines, which absolutely must be met to avoid catastrophe. These systems are also known as **mission-critical** systems. Systems that are shown to meet some explicitly stated statistical performance properties, where timeliness is not strictly guaranteed, are often referred to as **soft real time** systems. Systems where the statistical properties are implicit, unexamined and unstated, are known as **coincidentally real time** systems. This usage will be adopted in this report. According to this terminology, most real-time path-planning algorithms are coincidentally real time.

By contrast, the Dodger system described in this report, and the control algorithms it employs, are real time in the strong sense of the term. Dodger guarantees that it will avoid moving obstacles, it takes its own running time into account, and it solves a restricted version of the most commonly

[1](32, page 318).

studied problem in time-variant obstacle avoidance. The restrictions Dodger imposes on the domain are natural, reasonable and feasible. In addition, they are based upon the restrictions necessary to ensure that a safety-preserving path exists in the static version of the problem. The rest of this chapter reviews many of the major problems and results in gross motion planning, for both time-variant and time-invariant problems.

2.2 Static Obstacles in the Plane

Time-invariant problems were the central focus of path-planning research until the mid-1980's, and this remains an active research area. While initially focused upon the problems associated with moving a robot in a 2-dimensional space, path-planning research has since been generalized to include problems in N-dimensional "configuration space." The primary benefit of this generalization is that it has allowed researchers to develop upper-bounds for problems as diverse as the control of robot manipulators in factory environments, and navigation by an off-road vehicle over rough terrain, in both time-varying and time-invariant domains. However, it turns out that no general-purpose solution to the abstract problem has been found that has allowed researchers to move away from more narrowly focused solutions to particular problems. Thus, while there is a large body of literature developed around the more abstract problem, it is dwarfed by the work done on various aspects of the problem of manipulating a mobile robot through a set of immobile obstacles situated in a 2-dimensional space.

The abstract problem of moving a robot through a set of stationary obstacles is known as the "Piano Movers Problem" (76), or just the "Mover's Problem". It is also refered to the "Findpath Problem". Work by Lozano-Pérez (in, e.g., 56 (56), 57 (57)), extended the scope of the problem from the planar path-finding problem addressed by 65 (65), to a more general class of path-finding problems in **configuration space**. The configuration of an object is a set of parameters which, when taken together, are sufficient to describe the position of every point on the object. The set of all combinations of such parameters is the configuration space of the object. Obstacles are modeled as constraints on a robot's position in configuration space, and the space not occupied by obstacles is referred to as the **free space** of the robot. In addition to physical objects, this formalism allows any constraints on a robot's position, orientation or other configuration parameter, to be modeled as an obstacle in configuration space.

The roughly 30 years of research in this area can be partitioned into three or four basic approaches. **Roadmap methods** map the uncountably large set of possible robot motions into a network of one-dimensional lines, and thus reduce the problem to some form of graph search. **Cell decomposition** partions space into small cells, and searches for a path from the cell containing the starting position to a cell containing the goal location, where adjacent cells in the path adhere to some set of adjacency constraints. **Potential field methods** create "potential functions" that are designed to repel the robot from obstacles and towards the goal. It is generally recognized that, under the standard view of potential fields, they are best suited for the local decision-making associated with obstacle avoidance, and not particularly good at helping a robot achieve longer term goals. As a consequence, there has been research into the utility of **hybrid planners**, that integrate fast, "reactive" avoidance behaviors with some sort of more deliberative goal-achievement capability.

2.2.1 Roadmap Methods

Most roadmap methods are descended from the visibility graph approach employed in (65). Roadmap methods tend to be **complete**, in the sense that they are guaranteed to find safety-preserving paths when such paths exist. The basic approach is to collapse the uncountably large set of possible paths into a much smaller, usually finite, network graph, such that a path from a fixed location to a second goal location will exist on the network if and only if such a path exists in the larger set of all possible paths. 58 (58) are generally credited with formulating the "standard" problem, which involves manipulating a translating, but non-rotating, point robot in the plane. Representing the robot as a point can be accomplished via a technique introduced by 80 (80), whereby the polygonal obstacles in the environment are expanded by computing their Minkowski set difference with the robot. After this translation, the unobstructed paths in the transformed version of the problem are exactly the same as those in the original.

The size of a visibility graph is $O(N^2)$ in the number of obstacle vertices, and 4 (4) have shown how to find it in $O(N^2)$ time. 34 (34) describe an algorithm that takes time $O(K + N \log N)$, where K is the number of edges in the graph, and is typically much smaller than the worst-case of N^2. Once such graphs are constructed, they can be searched using standard graph-search techniques, such as A*, that support the efficient determination of resource-optimal paths, such as shortest time, shortest distance, etc.

A drawback with visibility graphs is that the vertices of the networks upon which they are based are obstacle vertices. Even when the obstacles have been "grown" from the original obstacles using the method of 58 (58), the implication is that such paths move the robot arbitrarily close to collision. While is can be shown that time and distance-optimal paths are a subset of such a network, it is often desirable to keep the robot at a safe distance from the obstacles. 66 (66) introduced the **retraction** method for motion planning, which uses generalized Vornoi diagrams to define networks that maximize the clearance between the robot and obstacles it must pass in order to get to the goal. The network defined in this fashion can be computed in $O(N \log N)$ time, and searched in the same way as a visibility graph. 13 (13) developed an $O(N^3)$ algorithm, based upon what he calls "generalized cones", in which "The paths are good in the sense that the distance of closest approach to an obstacle over the path is usually far from minimal." While the asymptotic runtime of this algorithm is not as good as that of 66 (66), and the performance properties much more vague, its actual runtime in uncluttered environments is apparently quite good. This algorithm was subsequently improved in 52 (52), by using a union of complex cones and convex polygons to represent free-space.

18 (18) developed the **silhouette method**, that generalizes the roadmap method to arbitrary dimensions. Basically, obstacles of n dimensions are projected onto curves of $n - 1$ dimensions, recursively, until a searchable network of 1-dimensional lines is produced. While the primary utility of this approach was to support a theoretical analysis of the complexity of motion planning, a version of this algorithm was implemented in (55). 7 (7) have recently analyzed roadmap methods, and established an upper bound on the problem that is $O(d^{k^2})$, where d is the maximum degree , and k is the number of variables in the semi-algebraic polynomials defining the search space.

2.2.2 Cell Decomposition

The basic idea of cell decomposition is to partition unoccluded space into a set of non-overlapping **cells**. When the union of these cells is exactly equal to the unoccluded space, we say the cell decomposition is **exact**, otherwise, it is **approximate.** Exact cell decomposition was used by 73 (73), to determine feasible paths for a line segment ("ladder"), which was free to rotate in the plane. In (74), this technique was used to establish a general-purpose, albeit very inefficient, path-planning method. The basic technique is to use algebraic curves to represent a robot's free space, and the primary benefit of this approach has been to establish theoretical upper-bounds for general classes of problems. As 54 (54) puts it, the upper bound on complexity which is established by 74 (74) is

> A free path in a configuration space of any fixed dimension m, when the free space is a set defined by n polynomial constraints of maximal degree d, can be computed by an algorithm whose time complexity is exponential in m, and polynomial in both n

("geometrical complexity") and d ("algebraic complexity") [2].

75 (75) give an $O(n^{2+\epsilon})$ algorithm for static planning problems in 3-dimensions, for any $\epsilon > 0$, by using an exact cell decomposition approach which they call **vertical decomposition**. This approach can be used for time-variant motion planning in 2-dimensions, but only if the maximum velocity of the robot is assumed to be unbounded.

A more practical approach, in terms of absolute runtime performance, has been to decompose the plane into a set of regular geometric shapes (e.g.,squares, rectangles, or hexagons), which do not generally allow the unoccluded free space to be represented exactly, and hence the name, "approximate" cell decomposition. As with exact cell decomposition, an adjacency relation is used to construct a graph which can then be search for a path. Most often, this approach is done hierarchically, and based upon rectangloids. The workspace is partitioned into cells at some initial level of granularity, and then cells are marked as either unoccupied, occupied, or "mixed" (neither totally occupied nor totally unoccupied.) Depending upon the algorithm, mixed cells can then be further partitioned, and the process repeated down to some predefined maximum granularity, or the graph can be searched for a solution prior to refinement.

Standardizing the shape of the cells greatly simplifies their computation, and in practice these methods have proven quite efficient. However, unlike exact cell decomposition techniques, which are complete, approximate cell decomposition may fail to find feasible paths. Approximate cell decomposition has been used in 2-dimensional static environments by a number of different authors, including 56 (56), 12 (12), and 42 (42). 81 (81) and 37 (37) extend the concept to 3-dimensional workspaces, and 56 (56) uses it for an abstract manipulator in a static environment.

2.2.3 Potential Field Methods

Another general approach to path planning involves defining a heuristic function defined on every represented position in free space. This function simply maps a robot's current location into a direction which the robot should move in order to make progress towards the goal. The most commonly used heuristics are known as potential field functions. Potential fields have low values at the goal, and high values at obstacle boundaries. Ideally, at all other points, they have intermediate values such that all paths slope towards the goal. Under this model, the robot's path-planning choice at any given location is simple: examine the immediate vicinity, and move to the location with the lowest potential field value.

The primary advantage of potential field functions is that they are very fast to compute. In fact, early applications of this technique to path planning can be found in (45; 46), in which a potential field function is employed to achieve collision avoidance in real time. This is one of the few studies in path planning that describes an algorithm that is real time in the strict sense of the term. The runtime performance of the algorithm and the frequency at which it is run are shown to be sufficient to ensure that the delay between sensing and servo-activation is sufficiently small in the worst-case that the results of the algorithm can always be employed to avoid obstacles.

50 (50) describes a potential field function that takes the robot's velocity into account, along with positional information. 2 (2) employs a potential field function that can be adapted dynamically at run time to reflect the changing goals of the planning agent, and uses this onboard an experimental robot. 14 (14) also uses a potential field function onboard an experimental robot. 63 (63) present a principled approach to the synthesis of potential functions, so that actuator limits can be accounted for in a general fashion. 10 (10) describe a potential field function, based upon a data structure instantiated at run-time, that they call a "virtual force field" (VFF). The author's real-time claims about this approach are based solely upon the dynamic nature of the VFF. By the terminology adopted above, this system is coincidentally real time.

[2](54, page 35).

Potential fields define a gradient over the workspace, and then gradient descent is used to find a path to the goal. 49 (49) identify four drawbacks to the general approach of potential field methods:

- Robots can become trapped in local minima.
- Potential field functions do not generally allow a robot to travel through narrow passages.
- Robots can oscillate between obstacles.
- Robots can oscillate in narrow passages.

11 (11) attempt to address these problems by extending the VFF approach to a new data structure called "vector field histograms"(VFH's), which addresses the oscillation problems, as well as the difficulties imposed by narrow passages. VFH's are coupled with a path monitor that detects traps, and a global path planner that directs the robot efficiently towards its goals. 51 (51) address the issue of local minima in a similar fashion, by integrating an artificial potential function with a cell decomposition-based technique which they call "path relaxation." 47 (47) provides a topological analysis of the conditions under which a potential field **cannot** be constructed so that no local minima exist. He then offers a class of "almost global" potential functions for a constrained version of the problem, for which all but a small subset of the points of the domain are on a gradient towards the goal.

2.2.4 Hybrid Path Planning

47 (47) has a more general perspective of potential fields than do most researchers. His work focused upon determining the limitations of potential field techniques. Thus, he assumes static problems, where the obstacle locations are known prior to runtime, and an unbounded computation that can be made "offline", prior to runtime, to determine the best possible potential field function to use at runtime. Configuration space is decomposed into cells of some fixed granularity, and then the set of all pairwise paths computed and stored in a data structure that enables a robot to quickly determine "where to go next", from any location, given any destination cell. This seems to be the basis of the gradient field approach suggested by 68 (68), but they provide insufficient detail or citations to be certain. However, these authors quite clearly distinguish between their gradient fields and potential field functions. As they put it,

> Another vector field type of representation, the artificial potential field, appears superficially very similar to the gradient field and it is also used for navigation and obstacle avoidance (2; 45; 50)...The computation of potential fields is generally based upon the superposition model, in which charges are distributed such that repulsive forces are generated near obstacles, and attractive forces are generated near goals...The resultant field, however, does not represent an optimal path, and may easily contain local minima and traps[3].

Under this prevailing view, potential functions are inherently local. Thus it is no surprise that they are much better at avoiding local obstacles than they are at steering a robot towards a distant goal. Incorporating global information takes time, and potential functions tend to be used precisely when time is of the essence. Research into the more strictly defined sort of potential fields has been largely abandoned, in favor of hybrid systems that use some sort of potential function for obstacle avoidance, and some other mechanism to steer the robot towards its goals. 59 (59) describes a promising decomposition approach that finds "channels" which are constructed so that gradient descent methods will take the robot to its goal. 3 (3) defines an architecture

[3](68, page 1376).

that allows the global influences of a robot's behavior to be taken into account by the more time-critical,"reactive" behaviors, which can also be viewed as potential field functions. 6 (6) integrate potential field functions with randomized search techniques, and 54 (54) describes a technique developed by 25 (25), which uses statistical methods to "learn" to avoid local minima. 22 (22) describe a potential field approach that explicitly addresses uncertainties in position, orientation and control. 60 (60) develop a hybrid architecture for integrating symbolic, reactive planning with control theoretic approaches to motion control.

In recent years, a number of authors have focused explicitly on the problem of obstacle avoidance, implicitly recognizing the fact that there is a place for both rapid, local reaction and more deliberate, global planning in most real-world planning applications. Many of these, such as (64), (40), (38), and (21), make some sort of real-time claim. For example, 21 (21) describe an impressive system for using visual information to recognize and avoid obstacles while the robot travels at relatively high speeds. As evidence of the real-time capabilities of the system, they state

> The robot has wandered around the lab at 30 cm/s for as long as 20 minutes without collision. To our knowledge, this is the first such demonstration of real-time wandering using only image motion cues.

Typically, as is the case with each of the papers cited above, the real-time nature of the approach stems from the dynamic nature of the problem. In other words, when not all of the obstacle data is known prior to plan execution, and must be somehow sensed at run-time, especially when a robot is simultaneously moving and avoiding obstacles, researchers often claim that their system is real time. (Not always, of course. For example, 27 (27) describe a technique used aboard a robot that safely navigates at 95 cm/sec in cluttered environments, and they make no use of the term "real time.") As noted above, in the absence of any statement of conditions required to maintain safety, whether they be hard or soft constraints, and the performance of the system with respect to such constraints, this is real-time avoidance in the loosest "coincidentally real time" sense of the term. As 61 (61) put it

> Real-time computing is **not** about building "fast" systems; it is about building systems that are predictably "fast enough" to act on their environments in well-specified ways.

There is no doubt that the primary utility of potential field functions, as well as the avoidance components of hybrid path planners, is derived from the fact that they are relatively fast to compute. However, there are very few papers in the path-planning literature that directly address the question of "fast enough". This becomes a fundamental issue when one considers the problems associated with avoiding moving obstacles.

2.3 Moving Obstacles

Many of the path-planning approaches referred to in the previous section were developed to apply in multi-dimensional domains, since even in time-invariant applications, the dimensionality of configuration space is generally greater than the three dimensions of the physical environment. Since a moving obstacle in n-dimensions can be represented as a static obstacle in $(n+1)$-dimensions, one might expect that these earlier results will naturally apply to time-variant domains. However, the temporal dimension is fundamentally different from the other dimensions in most configuration spaces, since it can be traveled in only one direction. It may be possible to modify some of the algorithms developed in the previous section to account for the unidirectionality of time, but there are no overt examples of this in the literature.

2.3.1 Static Path Planning in Time Variant Domains

Most of the research into path planning in time-varying domains has been on the static version of the problem, where all of the information required to plan is known to the planner in advance. This is the form of the problem introduced by 69 (69) as the **Asteroids Avoidance Problem**. In this problem, a point robot (in 1, 2, and 3 dimensional space) must find a path from a start location S to a goal location G, while avoiding a set of n constant velocity, polygonal obstacles. 69 give an algorithm for solving this problem that is exponential in the number of obstacles. In Section 3.1.1 (page 15), the conditions under which it is possible to guarantee safety in this problem are established. Chapter 5 (page 46) describes the Reif and Sharir algorithm in depth, and explicates many of its sub-problems that are treated as details in the original paper. The algorithm of (69) is complete, in the sense that it is guaranteed to find a path if it exists, and this early paper established an upper bound on the problem. In this paper, it is also shown that the time-invariant path-planning problem in three dimensions is $\mathcal{PSPACE}$-hard when the robot's ability to change velocity is bounded, and $\mathcal{NP}$-hard when it is not bounded. 17 (17) established that the Asteroids problem is $\mathcal{NP}$-hard in cases where the robot's velocity is bounded.

43 (43) present a heuristic solution to a slightly more general problem, in which obstacle trajectories are not constrained to be constant velocity, but are still known, and presumably computable. They also assume that some non-trivial set of obstacles will have zero velocity, and then decompose the problem into a two step process where 1) they find a collision-free path through the static obstacles and 2) they then attempt to find a set of speed assignments for the robot such that it can travel this path and avoid all moving obstacles. This approach is inherently incomplete, and is not guaranteed to find a path even when it exists. 28 (28) extend this approach to consider a set of "adjacent" paths, to prepare for cases in which step 2) is not successful.

24 (24) describe another heuristic technique for planning the motions of several moving objects in the plane. To do so, they treat the problem of planning the motion of a single moving object in the presense of time-varying obstacles as a sub-problem. Their solution is to partition the 3-dimensional configuration time-space into a finite set of 2-dimensional planes, and search for time-increasing paths in this partitioning using a visibility graph technique. Other than the fact that they consider the problem of planning several motions (which they "solve" by simply commiting to some heuristic, "priority" ordering), this approach is little more than an inexact, and hence incomplete, version of Reif and Sharir's exponential search. While it may be faster than the complete algorithm, since it considers fewer possible paths, it is still exponential in the number of obstacles.

29 (29) use a version of Reif and Sharir's algorithm to solve what is essentially the Asteroids problem, except that obstacles are allowed to move along piecewise linear trajectories. This algorithm runs in $O(n^2 \log n)$ time, but assumes that the robot's velocity is fixed and known in advance. This is useful when the robot happens to be able to move faster than all of the obstacles. 31 (31) exploit the triangle inequality to show that, in cases where the robot moves faster than all obstacles, a safety-preserving path to a goal exists, if and only if a safety-preserving path to the goal exists in which the robot always travels at its maximum speed. However, in cases where even a single obstacle can move faster than the robot, this property does not hold, and the utility of Fujimura and Samet's "accessability graphs" is greatly diminished, since it is not at all clear how it would be used to search over the set of all possible robot velocity assignments. Again, Chapter 5 (page 46) describes an algorithm based upon Reif and Sharir's seminal work, which generalizes the accessibility graph concept of 29 (29) to account for the fact that a robot typically has uncountably many choices of velocities that it may travel to get between two locations. In the general case, each of the nodes in the accessibility graph must be expanded from points in time-space to intervals in time-space. However, this introduces complications. Section 5.3 (page 49) develops a solution for the problem of finding what 29 call a **collision front**, in the case where the robot originates not from a point, but from an interval in time-space.

30 (30) use a cell-decomposition technique to solve a time-varying path-planning problem. Like all approximate cell-decomposition techniques, their solution is incomplete, and may fail to find a path, even when it exists. In order to ensure that paths are found, this technique should use relatively small cells. However, the search algorithm is exponential in the size of the cell-decomposition, in the worst-case. Thus, this approach is both incomplete, and asymptotically worse than the upper-bound established by 69 (69).

78 (78) show that, when obstacles are polygons constrained to move along piecewise linear trajectories, then free space can be represented by a closed set of non-overlapping polytopes, and that the algebraic nature of these polytopes can be exploited to use linear optimization techniques to search the space of potential paths. The principle advantage attributed to this approach is that it allows search for near-optimal paths, where optimality can be represented by an arbitrary linear constant. However, 20 (20) have shown that this algorithm is not complete, and thus it is not clear how much of an advantage this actually is. In addition, the algorithm is worst-case exponential in the number of obstacles, and the runtime performance for even small numbers of obstacles appears to be quite poor.

2.3.2 Dynamic Path Planning in Time-Variant Domains

The dynamic nature of time-varying domains has very rarely been considered in the path-planning literature, despite that fact that it is usually not the case that all of the requisite information will be available to the planner prior to run-time. 44 (44) focus upon the problem of how to avoid moving obstacles when their trajectories are sensed and must be extrapolated from observations. This work was very preliminary, used only two moving obstacles to test the concept and was concerned only with avoidance, and not goal achievement. 53 (53) present a systematic study of the problems inherent in **collision detection**, i.e., sensing and estimating the position and trajectories of moving obstacles, which could conceivably be the basis of a real-world, online path-planning system. They do not address the issue of finding paths, or even of avoiding collisions once they are detected.

35 (35) also addresses the problem of avoiding moving obstacles with unknown trajectories, where the trajectories are assumed to be piecewise linear, and the number of segments finite. He presents an $O(N^5)$ algorithm for solving this problem, where N is the number of obstacle vertices. However, the problem he addresses is one of navigating a point robot through a set of (presumably Minkowski sum-expanded) polygonal obstacles, which are constrained to never collide. This constraint amounts to requiring that no two moving obstacles ever move so close together that the robot cannot fit between them. 79 (79) outline a hybrid cell-decomposition/potential field technique for dynamic plan-planning in the presence of moving obstacles. Their algorithm on $O(p)$, where p is the length of the plan, but it assumes that there is one SIMD processor for each cell in the decomposed space. Like other potential field approaches, this approach is not complete, and best suited for avoidance, as opposed to goal achievement. 77 (77) analyze the expected path-execution time of path deviations made in response to the unexpected appearance of moving obstacles, when the set of "shelter" locations is known in advance.

2.4 Relationship of this Thesis to the Existing Literature

This report, examines the problem of guaranteeing safety in a dynamic, time-varying domain. It establishes necessary and sufficient conditions for guaranteeing safety in the static Asteroids Avoidance Problem, as well as sufficient conditions for doing so in the dynamic version of the problem. In all of the literature reviewed above, the path-planning problem has focused upon finding a solution **if a solution exists.** Prior to this report research, no one had addressed the issue of guaranteeing that a solution always exists.

This thesis describes Dodger, a system that solves a restricted version the dynamic Asteroids

Problem in hard real time. The domain restriction is natural, and derived directly from the constraints required to ensure that a safety-preserving path will always exist. When N is the number of obstacles known to the robot at any given time, the algorithm employed in this system is $O(N \log N)$ in the theoretical worst-case, but the observed worst-case behavior is better than linear in N. The avoidance algorithm has many of the advantages of potential field functions: it runs quickly and frequently, making decisions based upon its current view of the environment. However, this view is not local, and while the implemented system does not explicitly search through time, temporal projections are implicit in its computations. Based upon my review of the existing literature, this is one of the very few systems in path planning that is real time in a strict sense: it takes its own running time into account, and it is structured to ensure that decisions are always made quickly enough to guarantee that obstacles are avoided. It is the **only** work that has produced hard real-time solutions to problems in dynamic, time-variant motion planning.

Section 3.4 (page 28) shows that it is possible to guarantee that the robot can always make progress to its goals. The results of this section are the basis for one of three different goal-achievement algorithms that Dodger has been tested with. When Dodger uses this "heuristic," the overall algorithm is complete, since Dodger is guaranteed to eventually reach all of its goals, and it is also guaranteed to avoid all moving obstacles.

Chapter 3

Theoretical Foundations

It is tempting to adopt the following argument: the Asteroids problem has been shown to be $\mathcal{NP}$-complete (17; 18), so for even moderately large problems, it is not feasible to find solutions at all, let alone in real time. This chapter will show that even though the Asteroids Problem has been shown to be hard in the general case, finding solutions in low-order polynomial time is possible when the problem is restricted to ensure that solutions will always exist. This restriction turns out to be both natural and practical. The theoretical results developed in this chapter provide the foundation for the real-time capabilities demonstrated by Dodger. Chapter 4, will describe the algorithms that build upon the results of this chapter to allow Dodger to guarantee obstacle avoidance in real time.

3.1 The Asteroids Problem

This section will begin by considering a variant of the Asteroids Problem that is essentially the classical Asteroids Problem of, e.g., (69),(17) and (31). Typically this problem is cast as one of finding a path to a goal from a starting location, while avoiding moving obstacles. This is not strictly necessary: since all of the obstacles are moving in a straight line, it suffices to show that the robot is capable of getting to some one safe location, at which it can stop indefinitely without being hit. If this is the case, then eventually there will exist a linear, constant velocity, collision-free path to **any** goal location in the plane.

Starting with this statement of the problem, necessary and sufficient conditions for guaranteeing that the robot can avoid the obstacles are established. In subsequent sections, the implications of relaxing the assumptions of this form of the problem are examined. The first relaxation addressed is the "dynamic" asteroids problem, where the total number of obstacles that appear over time is unbounded, but the number of moving obstacles that are within some known distance of the robot at any given time is fixed. Then the problems presented by static obstacles are examined, and the techniques developed in the earlier parts of this chapter are extended to account for obstacles that do not move. The problem of accounting for the time it takes the robot to turn and accelerate is also addressed, as is guaranteeing safety when the trajectory of the obstacles is uncertain. The chapter concludes the by showing that it is possible to avoid obstacles while at the same time ensuring that the robot can make progress towards some goal location in the plane. [1]

3.1.1 The Static Asteroids Problem

For the purposes of this section, the "static" Asteroids Problem can be stated as: Given a robot, at initial location R, that is capable of instantaneous, unbounded acceleration, up to some maximum speed V_r, and a set of moving obstacles $O_1, O_2, \ldots O_n$, that move at known, constant

[1] Major portions of Section 3.1.1 and Section 3.1.2 have appeared in (48).

linear velocities, find a "safety-preserving" path that the robot can travel to avoid being hit by any of the obstacles.

The fundamental question which addressed in this section is:

> Under what conditions can one guarantee that 1) a safety-preserving path exists which will allow the robot to avoid being hit by any obstacle and 2) we can compute the path in time to execute it?

It is not obvious that such restrictions exist. However, shall be demonstrated, once we fix the number, speed and sizes of the obstacles, and the maximum speed of the robot, the obstacles can always be avoided, so long as they are each initially some minimum distance away from the robot. This distance will be refered to as the **threat horizon**, H. Ideally, we would like to make H as small as possible. Furthermore, it is not enough to know a path exists, we must be able to find it, and find it quickly enough to be able to execute it before being hit. These issues are all addressed in the proof of Theorem 1 below.

For the purposes of this section, the robot will be modeled as a single point and the obstacles as circles with diameters $d_1, d_2, \ldots d_n$. Most path-planning literature assumes that the robot and obstacles can be bounded by polygons. Reducing the robot to a point is a standard technique developed by 58 (58). It turns out that a solution in the case where the robot is a convex polygon is equivalent to the case where the robot is a point and the sizes of the obstacles have been increased by the size of the robot. However, this technique can only be used when the obstacles do not rotate. Since a polygon that does not rotate can be bounded by a circle, and a polygon that does rotate can also be bounded by a (possibly larger) circle, centered at the center of rotation, circles are used to represent obstacles in order to simplify the presentation, and actually gain some generality.

Theorem 1: Let R be a point representing the location of a robot at time t_0 in a 2-dimensional Euclidean plane. Assume that the robot can rotate and accelerate instantaneously, but is limited by a maximum speed V_r. Let $O_1, \ldots, O_n$ be a set of n circular obstacles with diameters $d_1, \ldots, d_n$ which move at known, constant velocities $v_1, \ldots, v_n$. Let V_o be the largest of the v_i. Let W be the sum of the widths of the obstacles, i.e., $W = \sum_{i=1}^{n} d_i$. If each of the obstacles is initially a distance greater than $\frac{W(V_o+V_r)}{2V_r}$ from R, then there exists a "safe haven" point S such that none of the O_i will touch S at any time, and the robot can move at constant linear velocity from R to S without intersecting any of the O_i.

Proof: Let Φ_i be the space occupied by obstacle O_i, from time t_0 to t_∞. Since the obstacles move along linear paths, Φ_i is comprised of all of the space between two parallel rays, separated by a width of d_i. Since the space which lies between two parallel lines is called a **plank**, this region shall be called a **half-plank** of width d_i.

If each of the obstacles begins at a distance greater than $W(V_o + V_r)/2V_r$ from R, then for each obstacle O_i, there must exist a positive number $\hat{\epsilon}_i$, such that O_i begins **exactly** $W(V_o+V_r)/2V_r+\hat{\epsilon}_i$ from R. Let $\epsilon = 2V_r\hat{\epsilon}_i/(V_o + V_r)$. Then ϵ is positive, $\hat{\epsilon}_i = \epsilon(V_o + V_r)/2V_r$, and O_i begins a distance $(W + \epsilon)(V_o + V_r)/2V_r$ from R.

Since the shortest distance between two points in a Euclidean plane is a straight line, the earliest time that one of the obstacles could intersect the robot would be in the case that the closest obstacle is moving at speed V_o, and it and the robot move straight towards each others, as depicted in Figure 3.1. In other words, the worst case is when that obstacle O_n for which $\hat{\epsilon}_n$ is the smallest of the $\hat{\epsilon}_i$, travels at speed V_o and heads directly towards R, while the robot travels a straight-line path towards O_n, at its maximum speed V_r. In this case, O_n and the robot would collide at time $t_0 + ((W + \epsilon)(V_o + V_r)/2V_r(V_o + V_r))$, which is just $t_0 + (W + \epsilon)/2V_r$.



Figure 3.1: Earliest-Collision Scenario

Now consider the region which comprises all of the points to which the robot could move by time $t_j > t_0$, while never moving at a speed greater than V_r. This area is just a circle, with radius $V_r(t_j - t_0)$. It follows that the area which comprises the locations to which the robot could travel before it could possibly be hit is a circle centered at R, with radius $V_r(t_0 + (W + \epsilon)/2V_r - t_0)$, which simplifies to $(W + \epsilon)/2$. We shall call the distance $(W + \epsilon)/2$ the **safety radius**, and the circle of this radius centered at R the **safety region**.

Now it must be shown that the n half-planks, $\Phi_1, \ldots, \Phi_n$, cannot completely cover the safety region. This follows from the 2-dimensional version of Bang's solution to Tarski's "plank problem" (5), which states[2]:

Theorem 2 (Bang): Let L be a convex body of minimal width l in a Euclidean plane of 2 dimensions. If L is contained in the union of p planks of widths $h_1, \ldots, h_p$, then $h_1 + \cdots + h_p \geq l$.

Clearly, the set of objects which can be covered by planks is a superset of the set of objects which can covered by half-planks. Since the safety region is a convex body of width $W + 2\epsilon$, by Bang's theorem, in order for the n half-planks to cover the safety region, $\sum_{i=1}^{n} d_i$ must be greater than or equal to $W + 2\epsilon$. But, by definition, $W = \sum_{i=1}^{n} d_i$, and ϵ is positive, so there must be some area within the safety region which is not covered by the Φ_i. This proves the existence of S. To see that the robot can move from R to S without being hit, one only need remember that the safety radius was defined so that it is possible for the robot to move anywhere in the safety region by the time the first obstacle reaches its perimeter. **Q.E.D.**

This proof satisfies the existence criteria. The robot will also need to be able to determine **where** a safe haven is in time to get to it, without compromising safety. Chapter 4 will describe one way to do this. For now, it is sufficient to note that this can be done in $O(n^2 \log n)$ time, where n is the number of planks. Once the actual safe haven is determined, computing a path to it is trivial, since the theorem guarantees that there is a straight-line path to the safe haven, and the robot is capable of traveling this path before it could possibly be hit by an obstacle.

To ensure that the robot can compute a solution in time to safely use it, we need to know the **actual** worst-case time required to compute the solution. Call this time t_s. If we increase H by the maximum distance an obstacle can travel in t_s, then we ensure that the system will have sufficient time to compute and execute the solution. Thus, the threat horizon, should be

$$V_o * t_s + W(V_o + V_r)/2V_r$$

to guarantee timeliness. Note that a similar argument can be used to account for robot rotation and acceleration times, in the more realistic cases where acceleration and rotation are not instantaneous.

3.1.1.1 The Necessity of the Threat Horizon

The previous subsection showed that constraining obstacles to begin their travels outside of the threat horizon H was sufficient to ensure the safety of the robot. This subsection will show that

[2] This theorem generalizes to n-dimensions.

the bound is tight, i.e., for any $H' < H$, there exist choices of V_r and V_o, and a configuration of obstacles such that a collision cannot be avoided.

Note that the size of the safety region depends only upon the sizes of the obstacles, while H also depends upon the ratio of V_o to V_r. This leads to the following theorem:

Theorem 3: Let R be a point in a 2-dimensional Euclidean plane, which represents the location of a robot at time t_0. Assume that the robot can rotate and accelerate instantaneously, but is capable of only a maximum speed V_r. Let $O_1, \ldots, O_n$ be a set of n circular obstacles with diameters $d_1, \ldots, d_n$, which move at known, constant velocities $v_1, \ldots, v_n$. Let $W = \sum_{i=1}^{n} d_i$, and let δ be a positive constant, such that $\delta > 2WV_r/V_o$. If at time t_0 obstacles are allowed to start a distance of no more than

$$(W - \delta)(V_o + V_r)/2V_r$$

from the robot, then there exist configurations for which it is not possible for the robot to avoid collision.



Figure 3.2: Necessity of the Threat Horizon

Proof: It suffices to show a single configuration for which it is not possible to avoid the obstacles. Let all the obstacles O_i have the same diameter D. Assume that the O_i start in the configuration depicted in Figure 3.2, where the obstacles are just touching (i.e. for $i < n$ the distance from the center of O_i to the center of O_{i+1} is D), and they are all traveling at speed V_o, along parallel courses as indicated in the figure. Let l_t be the line which is tangent to all of the obstacles at time t, and which is on the same side of the obstacles as it is at time t_0, when it is on the side of the obstacles nearest the robot. Let the distance from R to the line l_0 be $(W - \delta)(V_o + V_r)/2V_r$. Clearly, all of the obstacles are initially at least this distance from R at time t_0. The robot can travel the distance $(W - \delta)/2$ in time $(W - \delta)/2V_r$. When it has done so, the line $l_{(W-\delta)/2V_r}$ will be a distance $(W - \delta)/2$ away from the (original) point R. If the obstacles can travel the distance W before the robot can move $\delta/2$, then they will completely traverse the circle of radius $W/2$ centered at R before the robot is able to move outside of this circle. That is, if $W/V_o < \delta/2V_r$, the robot will be hit by at least one obstacle. Since, by definition $\delta > 2WV_r/V_o$, this completes the proof.

In cases where V_o is large relative to W and V_r, δ approaches arbitrarily close to 0. Consequently, $H = W(V_o + V_r)/2V_r$ is the minimum distance for which we can guarantee that a safety-preserving path exists, in the general case.

3.1.2 The Dynamic Asteroid Avoidance Problem

The previous section presented a necessary and sufficient criterion for guaranteeing safety in the classical "static" asteroid avoidance problem. In doing so, a functional relationship was established between the number, size, and speed of the obstacles, the maximum speed of the robot, and the distance which obstacles must initially be from a robot in order to ensure that the robot will never collide with any of the obstacles. The problem addressed thus far makes the same simplifying assumption as is made in, for example, (29; 30; 43; 69) : the position and the trajectories of the obstacles are known **prior** to execution time. While this formulation has proven challenging, it is overly optimistic. Normally, we can expect the existence, location, and trajectories of obstacles to become known only at execution time, perhaps while the robot is already in the process of avoiding previously detected obstacles. This section examines the problem of guaranteeing safety when the location of obstacles must be sensed at execution time, which is referred to as the "dynamic" Asteroid problem. Unlike the previous problem, under these conditions, it is not possible to compute a single safe haven and traverse a linear, fixed velocity path to it. Rather, a continuously evolving path must be determined as new information becomes available about the environment, and this must be done in such a way that safety is never compromised. Using Theorem 1, the next section develops a sufficient condition for ensuring the existence of a safety-preserving, piecewise-linear path in this problem.

3.1.2.1 Obstacles with Uniform Velocity

Consider the asteroids problem described above, where we know there are at most n circular obstacles $O_1, \ldots, O_n$, traveling along linear trajectories at constant speeds. For simplicity, assume that all of the obstacles are of the same diameter, D. In addition, assume that all of the O_i move at the same speed, V_o. Unlike the previous section, we do not assume that we know the location of the obstacles in advance. Instead, the obstacles are allowed to appear, one or more at a time, up to a maximum of n obstacles. We wish to determine a safety horizon, $\bar{H}$, such that we know that a safety-preserving path exists as long as all of the obstacles initially appear at a distance of at least $\bar{H}$ from the robot. The following is a corollary of Theorem 1 above:

Corollary 1: Let H be $W(V_o + V_r)/2V_r$, where $W = nD$, V_r is the maximum speed of the robot, and V_o is the (uniform) speed of the obstacles. If each of the obstacles O_i appears at some time $t_{a(i)} \geq t_0$, at a distance greater than $\bar{H} = nH + W$ from the position of the robot at that time, then there exists a piecewise linear, collision-free path from the starting point R to some point S such that none of the O_i will touch S at any time.

Proof (by induction on m, the number of obstacles that have already appeared[3]) The base case is handled by Theorem 1, since $nH + W \geq H$, and we can assume that $t_{a(1)} = t_0$.

Assume, by induction, that after the first $m < n$ of the obstacles have appeared, there exists a safety preserving path to some point S_m which is safe from all of the obstacles $O_1, \ldots, O_m$. Let R_x be the location of the robot at time t_x. If at time $t_{a(m+1)}$ all of the obstacles $O_1, \ldots, O_m$ are farther than H from $R_{a(m+1)}$, then once again Theorem 1 holds, and a safety preserving path exists from $R_{a(m+1)}$ to some point S_{m+1}. If one (or more) of the O_i is within H of the robot, then the robot can wait at S_m until those obstacles have traveled at least a distance H from S_m. In the worst case, this time is $(H + D)/V_o$. Of course, another obstacle could move to within H of S_m in this time. Since there are only $m < n$ obstacles, the longest we would have to wait would be $m(H + D)/V_o$ before we can be assured that all of the obstacles are at least H from S_m. In this worst-case, the most recent obstacle, O_{m+1} will still be a distance greater than $(nH + W) - m(H + D) = n(H + D) - m(H + D) = (n - m)(H + D)$ from S_m, and since $m < n$, we know that this distance is greater than H. Thus we know that at some time, all of the $m + 1$ obstacles will be outside of the safety region, and so Theorem 1 applies. Thus there exists a (linear) path from S_m to some new point S_{m+1}. **Q.E.D.**

Since by definition $W = nD$, it follows that $\bar{H} = n^2 D((V_o + V_r)/V_r + 1)$, and thus this corollary gives an $O(n^2)$ upper bound for the threat horizon in the dynamic asteroids problem. It is also easy to see that $\bar{H}$ is sufficient to guarantee safety so long as there are never more than n obstacles within $\bar{H}$ of the robot R at any single time, even if many more than n obstacles appear over time.

3.1.2.2 Allowing the Speed of Obstacles to Range from V_l to V_o

There is a straightforward generalization of the above theorem in cases where the obstacles are constrained to have constant positive velocities ranging from a lower bound of V_l to a maximum speed of V_o.

Corollary 2: Let $O_1, \ldots, O_n$ be n circular obstacles of fixed diameter D, each constrained to move at a constant linear velocity, V_i, such that $\forall i\ V_l \leq V_i \leq V_o$, where V_l and V_o are fixed positive constants. Let $W = nD$, and H be $W(V_o + V_r)/2V_r$, where V_r is the maximum speed of the robot. If each of the obstacles O_i appears at some time $t_{a(i)} \geq t_0$, at a distance greater than

$$\bar{H} = \frac{V_o(nH + W)}{V_l}$$

from the position of the robot at that time, then there exists a collision-free path from the starting point R to some point S such that none of the O_i will touch S at any time.

Proof (by induction on m, the number of obstacles that have already appeared): The base case is again handled by Theorem 1, since that theorem applies whenever obstacle velocities are constrained by some maximum, V_o, and obstacles occur outside the threat horizon H. Since $V_o \geq V_l$, it follows that, for all values of n, $V_o n/V_l \geq 1$, and thus $\bar{H} > H$.

The inductive step is very similar to that for Corollary 1: Assume, by induction, that after the first $m < n$ of the obstacles have appeared, there exists a safety preserving path to some point S_m which is safe from all of the obstacles $O_1, \ldots, O_m$. Let R_x be the location of the robot at time t_x. If at time $t_{a(m+1)}$ all of the obstacles $O_1, \ldots, O_m$ are farther than H from $R_{a(m+1)}$, then once again Theorem 1 holds, and a safety preserving path exists from $R_{a(m+1)}$ to some point S_{m+1}. If one (or more) of the O_i is within H of the robot, then the robot can wait at S_m until those obstacles have traveled at least a distance H from S_m.

[3] This is not induction on n, the maximum number of obstacles that can appear.

In the following, the earlier proof must be changed to account for the fact that slower moving obstacles may remain near the robot for longer periods of time: In the worst case, this time is $(H+D)/V_l$ (note that $(H+D)/V_l \leq (H+D)/V_o$, which was the worst case in the previous proof). Again, another obstacle could move to within H of S_m in this time. Since there are only $m < n$ obstacles, the longest we would have to wait would be $m(H+D)/V_l$ before we can be assured that all of the obstacles are at least H from S_m. In this worst-case, the most recent obstacle, O_{m+1} can travel a distance of up to $V_o * m(H+D)/V_l$ (if it happens to have the maximum speed, V_o). In any case, then, this will still be a distance greater than $V_o * (nH+W)/V_l - V_o * m(H+D)/V_l = (n-m)V_o(H+D)/V_l$ from S_m, and since $n > m$, and $V_o \geq V_l$, we know that this distance is greater than H, and Theorem 1 applies. Thus there exists a (linear) path from S_m to some new point S_{m+1}, which is safe with respect to all of the currently visible obstacles. **Q.E.D.**

3.1.3 Tighter Bounds

Note that this threat horizon grows with the ratio of the maximum speed to the minimum speed of obstacles, V_o/V_l. If this number is large, the size of the horizon becomes prohibitive. Intuitively, slower moving obstacles should be easier to avoid, but in the context of this result, allowing the speed of obstacles to approach zero will make the threat horizon approach infinity. This is a clear indication that the bound is not tight. Even in the case where $V_o = V_l$, H is chosen to account for the case when all n obstacles are a distance H from the obstacle. That is, the worst-case scenario for the static problem occurs when all of the obstacles will occupy the safety region at roughly the same times. In such cases, the robot must find a location that is a safe haven with respect to all obstacles. When obstacles are more spread out, it may be possible for the robot to find safety-preserving paths where no locations it moves through are safe havens with respect to all obstacles. Ultimately, a location that the robot passes through need only be safe at the time the robot occupies it. A safe haven is defined to be a location that is safe with respect to a given set of obstacles at **all** times.

$\bar{H} = nH + W$ is chosen to account for the times when the n obstacles are "evenly" spaced. That is to say, it was constructed to ensure that, no matter what the configuration of obstacles when a new obstacles approaches within $\bar{H}$ of the robot, there will eventually be a time that **no** obstacles will be within H of the robot. Then, Theorem 1 can be applied, and a linear, constant velocity path to a safe haven is guaranteed to exist. When all the O_i are going to occupy the safety region at roughly the same time, a threat horizon of H alone is sufficient. When the obstacles are evenly spaced, so that exactly one is within H of the robot at any given time, then a horizon of $H' = \bar{H}/n = H + D$ will suffice, since the robot will be able to dodge each obstacle one at a time, by simply moving (at most) half the width of that obstacle. This observation may allow us to reduce the threat horizon by a constant factor, but the resulting distance will still be quadratic in the number of obstacles. I believe that a threat horizon exists that is asymptotically better than $O(n^2)$ in the number of obstacles, but I have been unable to prove or disprove this conjecture. Section 7.4 (page 78) presents empirical evidence that supports this conjecture.

3.2 Stationary Obstacles

When the speed of obstacles is allowed to be zero, then the threat horizon $\bar{H}$ of Corollary 2 goes to infinity. A different approach must be used in order to account for the presence of stationary obstacles. This section, examines ways in which the concept of the threat horizon can be extended to account for the additional complexities caused by stationary obstacles. First, it shows how the safety radius can be expanded to account for the presence of stationary objects, while still guaranteeing the existence of a safe haven. Then this section examines how to adjust the threat horizon to reflect the worst-case time required to travel a possibly-obstructed path to safety. In both cases, it is easy to find upper bounds which are sufficient to guarantee safety. Finally, it is shown that while these bounds are not tight, domain analysis can often allow more reasonable worst-case bounds to be established.

3.2.1 Increasing the Size of the Safety Region

In the proof of Theorem 1, it was sufficient to show that an arbitrarily small safe haven existed. In order to guarantee the existence of a safe haven in the presence of both moving and stationary obstacles, we must adapt the approach to ensure that our potential safe haven is not going to be occupied by stationary obstacles. Assuming initially that all that is known about the stationary obstacles is their total area, α, how large must the safety radius be so that the existence of a safe haven can still be guaranteed? If all one knows is the area occupied by the stationary obstacles,



Figure 3.3: Determining the Safety Radius

then the safety region must be expanded so that its area is larger than the worst-case area occupied by the moving obstacles, plus α, the area occupied by stationary obstacles. This is not as simple as calculating the area, A, occupied by the safety region needed in the absence of stationary objects, and increasing the safety radius R, of this region to $\bar{R}$, such that $\pi \bar{R}^2 = A + \alpha$. This is because, as the safety radius increases, the worst-case area occupied by moving obstacles also increases. We want to find the radius of a circle so that, if all of the obstacle half-planks cover the circle, there will always be an area of size greater than α that is not covered.

Consider Figure 3.3. Recall that W is the sum of the widths of the obstacles. From Bang's Plank Theorem, it follows that the largest area of a circle that can overlap the obstacle half-planks is the area between two parallel lines each $W/2$ from the center of the circle, since this is the largest convex object of minimum width W that lies completely within the safety region. Let us call this area ω. In Figure 3.3, it is the part of the circle that is not shaded. We want to find a safety radius R such that $\pi R^2 > \alpha + \omega$. This is complicated by the fact that ω is itself a function of R. If its center is at the origin, the equation for a circle of radius R is just $R^2 = x^2 + y^2$. Equivalently, $y = \sqrt{R^2 - x^2}$. From Figure 3.3, it should be clear that

$$\alpha = 4 \int_{W/2}^{R} \sqrt{R^2 - x^2}\, dx$$

Integrating this yields

$$\alpha = \pi\, R^2 - \frac{W\, \sqrt{4\, R^2 - W^2}}{2} + 2\, R^2\, \arctan(\frac{W\, \sqrt{4\, R^2 - W^2}}{-4\, R^2 + W^2}) \tag{2.1}$$

Unfortunately, there is no obvious way to obtain a closed-form solution for R in terms of α and W. However, this can be solved iteratively, especially since we do not need an exact value for R : **any** value larger that the exact solution will guarantee the area is at least as large as required. A similar form of this equation will also be used later, in Section 4.2, which shows how Monte Carlo methods can be used to find the safe haven.

3.2.2 Finding a Path

A number of authors have examined the problem of determining a path through some set of stationary obstacles, e.g., (13; 66; 43; 42), and solutions have been found with time complexities as low as $O(n \log n)$, where n is the number of vertices of the obstacles. This section adopts the traditional assumptions that robots are holonomic and travel along piecewise-linear paths. One common method for solving the find-path problem is the visibility graph approach used by 58 (58), which will be briefly sketched.

Assume that all obstacles are modeled as convex polygons, and call the set of polygonal edges S. A visibility graph of S is a graph that has a node for each endpoint of every segment, and an edge between nodes v_0 and v_1 if

1. v_0 and v_1 are adjacent vertices on the same obstacle, or
2. v_0 and v_1 are on different obstacles, and the open segment (v_0, v_1) does not touch any segment in S.

In other words, an edge between v_0 and v_1 exists in the graph if the straight-line path between the two vertices does not pass through an obstacle. Figure 3.4 shows a simple example of a visibility graph. The edges corresponding to the edges of the polygons A,B, and C are in the graph because of the first condition above, and the edges

$$A_2B_1, A_4B_3, A_3B_1, A_3B_3, B_2C_1, B_2C_2, B_2C_3, B_4C_1, \text{ and } \; B_4C3 \tag{2.2}$$

are in the graph due to condition 2.

Several algorithms are known for finding the visibility graph on a set of line segments in time $O(n^2)$, where n is the number of vertices in the set S. 34 (34) describes an algorithm that takes time $O(k + n \log n)$, where k is the number of edges in the graph.

To use visibility graphs to solve the find-path problem, add the robot's location, R and a destination G into the set S of segments that delimit obstacle boundaries. Then compute the visibility graph for these vertices. A version of Dijkstra's algorithm (23) for single-source shortest



Figure 3.4: A Visibility Graph

paths can then be used to find the shortest path from R to G that does not pass through the interior of an obstacle. This computation can be performed in $O(n^2)$, so the overall path-planning problem can be solved in $O(n^2)$.

It is therefore a straightforward matter to bound the computation time required to find a path to a safe haven with some function quadratic in the number of obstacle vertices. But to guarantee that the robot can avoid all moving obstacles while negotiating a path through some set of stationary obstacles, we also need to be able to bound the path **execution** time, in order to ensure that the robot can sense incoming moving obstacles soon enough to move out of their way. This amounts to finding the longest minimum-length path between any two points within the safety radius. In general, even when the area occupied by the obstacles is known and fixed, this distance can be made arbitrarily long. For an intuition on why this is, consider Figure 3.5, which shows how such a long path could be constructed. If we assume that moving obstacles cannot penetrate into the interior of static obstacles, a robot would not have to travel arbitrarily far into the interior of a concave obstacle in order to avoid an obstacle traveling along a linear trajectory of fixed velocity. So it may be possible to bound the distance a robot would have to travel by limiting the set of origination and destination points to those that are either reachable by obstacles, or not reachable by a moving obstacle, but arbitrarily close to locations that are reachable.

Another way to simplify this problem is to assume that all stationary objects are convex. This is not as strong an assumption as it might seem: first, it merely requires us to eliminate from consideration as a safe haven any point inside a concavity of an obstacle. This, in turn implies that the effective area of the obstacles will increase.

Define the width of an obstacle to be the maximum distance between two points on its exterior. If all obstacles are concave, and we allow them to touch, then the most they can force the robot to deviate from a straight-line path between two points is at least half the sum of their maximum widths, as shown in Figure 3.6(a). Exactly how much more than this R may be diverted is unclear, but appears to be bounded by the width of the largest obstacle. In any case, the total diversion is certainly less than the sum of the widths of the obstacles.

Of course, allowing obstacles to touch is the same as combining them into a single obstacle. If we assume for this reason that all distinct obstacles are disjoint, determining the worst-case



Figure 3.5: An Arbitrarily Long Path in the Interior of an Obstacle



(a) Obstacles Allowed to Touch (b) Obstacles Not Allowed to Touch

Figure 3.6: Obstacles Forcing Long Diversions

obstruction is greatly complicated. First note that "thin" obstacles actually force more diversion than "rounder" obstacles. Figure 3.6(b) shows that the general solution is at least $W * \lfloor\sqrt{N}\rfloor$, where W is the width of the greatest obstacle, and N is the number of obstacles.

This assumes that all obstacles are of equal width, and that they are very much wider in one direction that in the other (perpendicular) direction. They can, in fact be made arbitrarily narrow, and arbitrarily close together. In this example, the robot is forced to travel a distance of roughly $4W$ in addition to the distance from R to G. Whether one can force a diversion of worse than $W\lfloor\sqrt{N}\rfloor$ is an open question, which involves reasoning about all the possible deployments of all the possible shapes and sizes of obstacles.

In practice, though, it is hard to imagine having information about the number, width and area of stationary obstacles without knowing something about their deployment. Assuming that we do have an upper bound on the time it will take the robot to travel the (worst-case) path to safety, it is straightforward to extend the threat horizon by a corresponding amount. If the worst-case extra distance that the robot can travel due to obstruction by moving obstacles is D, then the time the robot will take to travel this distance is D/V_r, and the threat horizon needs to be increased by the distance the fastest obstacle can travel in this time, i.e., $D * V_o/V_r$.

3.2.2.1 Turning and Accelerating

It is also interesting to ask what effect the obstacles can have on the number of turns that the robot is forced to make. This is relevant, because physical robots will need to account for the time required to make such turns, in addition to the time need to travel the path. Assuming that the obstacles are convex polygons, then clearly we need make no more than $\lceil (V+1)/2 \rceil * N$ turns, where V is the number of vertices in the obstacle with the most edges[4]. However, the actual bound appears to be much lower. If we adopt the conjecture suggested above that $\lfloor \sqrt{N} \rfloor$ bounds the number of non-touching obstacles that the robot can be forced to circumvent in the shortest path from R to G, then it follows that the robot need make no more than $\lceil V/2 \rceil * \lfloor \sqrt{N} \rfloor$ turns.

If the time required to turn is high, it may be worth "expanding" the obstacles by enclosing them in rectangles, and not allowing the robot's path to enter any rectangle (except perhaps to terminate). By doing this we can ensure that the robot need never take more than 3 turns per obstacle: one when it reaches the corner of the enclosing rectangle and turns towards one of the two adjacent vertices, another when it reaches that vertex and turns to traverse the next edge, and the third when it leaves the edge. Again, whether this is a worthwhile approach is highly domain-dependent.

Once the worst-case number of turns is established, adjusting the threat horizon is again simply a matter of extending it to account for the time it will take the robot to execute these turns.

3.3 Changing Velocities and Uncertainty

Up until this point, I've assumed that all obstacles travel at known, constant velocities. Allowing obstacles to change speeds does not alter the fundamental results of Theorem 1 (page 16) or Corollary 2 (page 20). However, accounting for obstacles which can deviate from a straight-line path transforms the problem considerably. If the trajectory of an obstacle is known but non-linear, the problem becomes one of finding the equivalent of Bang's Plank Theorem for whatever curves the various obstacles trace in the plane, i.e, we can use the same technique as used in Theorem 1 if we can accurately characterize the largest circle which the various obstacle paths can completely cover.

Allowing for the case where the actual path of the obstacle is not known to the robot is much more difficult. To begin with, if the obstacles can travel faster than the robot, and are able to change their direction without any restrictions, it is not possible to guarantee avoidance of even a single obstacle. So, we need to assume some bounds on the ability of the obstacles to change course.

One way to do this is to bound the change in direction as a function of time. If we limit an obstacle's ability to deviate from an initial direction θ_0 with a maximum angular velocity of ω, what can we say about the robot's ability to avoid obstacles? To begin with, at time $t = \pi/\omega$, an obstacle can make a turn of 180 degrees, or in other words, after this time, it could be heading in **any** direction, and for this reason, no point in the plane can be considered a permanent safe haven with respect to even a single obstacle. This does not mean that such obstacles cannot be avoided, it only means that, given enough time, any obstacle can get to any fixed point in the plane. Is it possible to adjust the threat horizon to allow for even slight changes in course?

Consider this approach: The set of points possibly occupied by the obstacle after time t is shown in Figure 3.7. The inner, dotted lines represent the boundaries of the obstacle's position at times between t_0 and a fixed point in time t. For simplicity, assume that θ_0 is 0, and that R is at the origin. Then the two dotted lines of Figure 3.7 are actually arcs of circles, which represent the path traveled by the robot if it moves at its maximum velocity while turning constantly at a rate of ω (or

[4]Not so clearly, this can be made $\lceil V/2 \rceil * N$ as long as we are careful to travel from vertex-to-vertex when moving from one obstacle to the next.



Figure 3.7: Approximating the Area Occupied by an Obstacle Whose True Trajectory is Not Known

$-\omega$). As noted above, the robot will turn 180 degrees in time π/ω, so it will complete the circuit in twice this time, i.e., $2\pi/\omega$. If the robot moves at maximum speed V_r, then the circumference of this circle is $2\pi V_r/\omega$, and the radius is therefore ω/V_r. Thus the equations for the two circles are

$$x^2 + (\omega/V_r - y)^2 = (\omega/V_r)^2 \tag{3.1}$$

$$x^2 + (-\omega/V_r - y)^2 = (\omega/V_r)^2 \tag{3.2}$$

We can use the outer lines as conservative estimates for the space occupied by an obstacle through time t. Using this (over)estimate, note that an entire half-plane can be covered by N obstacles, if the threat horizon $\bar{H}$ is greater than $V_o * \pi/N\omega$, as shown in Figure 3.8. This provides an upper bound on $\bar{H}$.

The outer lines are defined as follows

$$x = x_0 + t * V_o * \cos\theta \pm \omega$$

$$y = y_0 + t * V_o * \sin\theta \pm \omega$$

After time t, the angle $\angle ARC = \angle BRC = \omega t$. The distance $RA = RB = RC$, and is just $V_o * t$. Thus $\triangle ARC$ and $\triangle BRC$ are both isosceles, and by the Law of Sines, their base is equal to $2tV_o \sin\omega t$. If we model the region occupied by each obstacle as a plank of width $4tV_o \sin t\omega$, the we can use the previous results of Theorem 1 (page 16), and Corollary 1 (page 19) to determine a safe harbor with respect to any obstacle no farther than tV_O away from the robot. In the static case, where we are given the initial position of a set of obstacles and asked to find a safe haven with respect to them, this approach cannot be used. Somewhat paradoxically, as we move the position of obstacles farther and farther back, even though they become easier for the robot to avoid, the set of points which they could possibly hit becomes larger and larger, and as noted above, a single obstacle a distance of $V_O\pi/\omega$ away will cover an entire half-plane. We were able to adopt this strategy in the dynamic case, since we needn't worry about obstacles arbitrarily far away. As long as the robot can sense the position of an obstacle as it enters the expanded threat horizon $\bar{H}$, it has a strategy for avoiding it.



Figure 3.8: Plane Covering By 6 Obstacles Due To Uncertainty

Recall that the threat horizon, $\bar{H}$ was defined in Corollary 1 to be

$$n * W(V_o + V_r)/2V_r + W$$

In that formulation, W was the sum of the widths of the obstacles. We need to change this to reflect the "growth" caused by uncertainty, i.e,

$$W' = W + n4tV_o \sin t\omega$$

The resulting threat horizon is

$$\bar{H} = (W + n4tV_o \sin t\omega)(V_o + V_r)/2V_r + W + n4tV_o \sin t\omega$$

Unfortunately, t is a function of $\bar{H}$, i.e., $t = \bar{H}/V_o$. In other words, we need to solve for t, such that

$$t = ((W + n4tV_o \sin \omega t)(V_o + V_r)/2V_r + W + n4tV_o \sin \omega t)$$

and there is no closed-form solution to this equation. Again, we can use iterative methods to find t, if it exists. In practice, this technique will only work for small values of ω. Remember, however, that in cases where α is unbounded, we cannot guarantee to avoid even a single obstacle. These results show that it is possible to avoid a belligerent obstacle that can move faster than the robot, if the obstacle's ability to turn is limited. One should keep in mind that the **actual** width of the obstacles does not change, and this choice of threat horizon is very conservative. Consequently, if we are willing to sacrifice guarantees on the robot's ability to find a safe haven, in favor of accepting some arbitrarily small but non-zero risk, we can expect to reduce the threat horizon considerably.

3.4 Goals of Achievement

The Asteroids problem addressed in (69),17, and (18) is one of finding a path from a starting position to a single goal position while avoiding all moving obstacles. So far, only with the problem of avoidance has been considered. Recall, that these papers both addressed the "static" problem, where the positions of all the moving obstacles were known, and the robot was charged with finding a single safety-preserving path. In this formulation of the problem, it is sufficient to find a path to a single safe haven, since the robot can wait there indefinitely, until the obstacles move out of its way and a safe path presents itself. It follows from this and Canny's $\mathcal{NP}$-completeness result (18), which shows that the Asteroids Problem is $\mathcal{NP}$-complete, that the problem of finding a safe haven and a path to it must also be $\mathcal{NP}$-complete.

In the dynamic asteroids problem, where any number of obstacles are allowed to appear over time, subject to some limit on the number within a fixed distance of the robot, the situation is less clear. One can imagine scenarios where the obstacles somehow conspire to keep the robot away from the goal. Since the target is fixed, we may not be able to ensure that the robot can ever get to it. However, it turns out that it is possible to find a threat horizon that will guarantee the robot's ability to make progress to the goal, and this in turn allows us to ensure that the robot **is** eventually able to move safely to any target location, as long as all obstacles are constrained to appear outside the threat horizon.

Corollary 3: Assume a fixed goal position G. Let $H = W(V_o + V_r)/2V_r$ be the threat horizon determined in the **static** case of Theorem 1 above. Let $\bar{H} = nH + W$ be the threat horizon of the dynamic case in Corollary 1. Finally, let $\bar{H}_G = 2\bar{H}$. If all obstacles are constrained to appear a distance $\bar{H}_G$ from the robot, then whenever a new obstacles appears, there exists a collision-free path from the robot's initial position at R to some point R' such that the $distance(R', G) < distance(R, G)$.

Proof Recall that the set of points that the robot can get to in a fixed time t is a circle of radius $t * V_r$. Furthermore, recall that the static threat horizon H ensures that the robot is able to move a distance $(W + \epsilon)/2$ before an obstacle appearing outside of the threat horizon could possibly hit it. Clearly, doubling H will double this distance, so for a threat horizon of $2H$, the robot will be able to move to any point within a circle of radius $W + \epsilon'$ before possibly being hit by an obstacle which starts at a distance outside of this horizon.

Now, for fixed and distinct points R and G, consider the set of points that are closer to G than R. This is the set of points bounded by, but not including, the circle centered at G whose radius is the distance from R to G. It follows that the set of points which are closer to G than R, and to which we can guarantee that the robot can safely travel, is the intersection of this circle with the safety region.

If G is within the safety radius, then the robot can clearly make progress to G: in fact, it can safely travel to G without being hit (by the definition of the safety radius and Theorem 1). So we can assume, without loss of generality, that G is outside of the safety region. Let C_S be the circle of radius $W + \epsilon$ centered at R, and let C_G be the set of points that are closer to the goal G than the robot at point R. The set of points $C_G \cap C_S$ cannot be covered by the half-planks representing the location of the obstacles over time. To see this, first note that the area occupied by $C_G \cap C_S$ increases with the distance from R to G. Therefore, this area is smallest when G is as close to R as possible, i.e., just outside the safety radius of $W + \epsilon$. Now consider Figure 3.9. The parallelogram $\square RI_0GI_1$ can be inscribed within the region. $C_G \cap C_S$, and all of the edges, $RI_0, I_0G, GI_1,$ and $I_1, R.$ are of length $W + \epsilon$, as is the segment GR. From the Pythagorean Theorem, it follows that the height of the equilateral triangles $\triangle\, GI_0R$ and $\triangle\, GI_1R$ is $\sqrt{3}/2(W + \epsilon)$, and hence segment I_0I_1 is of length $\sqrt{3}(W + \epsilon)$. Thus $\square RI_0GI_1$ has width $W + \epsilon$, and so does the region $C_G \cap C_S$. From Bang's Plank Theorem, it follows that the half-planks representing the paths of the obstacles over time cannot cover this region. Consequently, some part of $C_G \cap C_S$ is a safe haven w.r.t. any of the obstacles which appear a distance of at least $2H$ from R.

Now consider the proof of Corollary 1. If we expand the threat horizon H to $2H$, then at any step in the induction where the robot chooses a safe haven, we can guarantee that the robot can choose a safe haven that is in the region $C_G \cap C_S$, since we have shown above that even when this region is smallest, the obstacles cannot cover all of it. The threat horizon $\bar{H}_G = 2\bar{H}$ was chosen



Figure 3.9: The Smallest Intersection of the Safety Region with the Set of Points Closer to G than R

to reflect the necessary increase from H to $2H$ in the proof. It follows that every time the robot chooses and moves to a safe haven, it reduces its distance to the goal.

One of the heuristics that Dodger uses to decide where to go if it cannot find a constant velocity path to its goal is based upon this result. Chapter 7 compares the results of using this approach to those achieved by employing other heuristics. The primary drawback to this approach is that the threat horizon must be extended in order to ensure that a safe haven which is closer to the goal than the robot's current position will always exist. Chapter 7, also examines the effects of shortening the threat horizon below this theoretical minimum. Shortening the horizon implies that safety can no longer be guaranteed, but it would be a straightforward matter to modify Dodger to look first for safety in the general direction of the goal, and only consider moving away from the goal if this is not feasible.

3.5 Summary

This chapter has established a theoretical foundation for real-time obstacle-avoidance. The concept of the threat horizon is central to assuring that a robot will be able to avoid all of the moving obstacles that it encounters, and it also provides the basis for a control regimen that can take the run-time requirements of an obstacle-avoidance algorithm into account. In essence, one can account for the time required to compute a reaction to a newly sensed obstacle simply by extending the threat horizon by the maximum distance that an obstacle could travel while the result is being calculated. Dodger has demonstrated the feasibility of this approach.

After establishing the existence of a threat horizon for the static Asteroids Problem, basic result was extended into cases where 1) the positions and trajectories of the obstacles become known to the robot over time, 2) where there are stationary obstacles as well as moving obstacles, and 3) where obstacles are not restricted to having fixed velocities. This chapter has also shown how it is possible to construct a threat horizon such that the robot is guaranteed to be able to make progress towards the goal. The next chapter will describe some of the algorithms required to put this theory into practice.

Chapter 4

Dodger Algorithms

The Dodger system demonstrates that it is possible for a computer program to be intelligent **in** hard real time: it solves the dynamic asteroids problem in real time, guaranteeing that moving obstacles will be avoided. To do this, the problem has been decomposed into two separate problems: a "critical" component, which ensures the safety of the system, and a non-critical component, which focuses on finding paths from the robot's current position to the location of a goal. Corollary 1 (page 19) establishes the minimum conditions necessary to ensure that the robot will always be safe, and it also provides a blueprint for how this should be done. Dodger employs an algorithm based upon this result to guarantee that the sensing and calculating needed to avoid obstacles will always be performed in time for the simulated Dodger robot to actually avoid them. This algorithm runs quickly at regular intervals, and even in the worst case, it completes in a fraction of a second.

This reactive, hard real time capability is all Dodger needs to avoid obstacles. However, Dodger is also expected to find and traverse paths to randomly generated goals. Consequently, Dodger must also solve the find-path problem. Currently, Dodger employs local decision-making routines to guide it towards its goals. Each of these routines produces acceptable behavior in real time, and one of them is complete, in the sense that it guarantees that paths will be eventually be found whenever they exist. While not complete, the other two heuristics have proven adequate in practice, and actually outperform the complete routine in the number of goals the Dodger is able to achieve over time.

In theory, is possible to use an exhaustive search routine that is guaranteed to eventually find a solution in all configurations. In many cases, this search will find a solution quickly. However, in the worst case, the time required to find a solution will be such that the search is obsolete before it has finished. In such cases, the search can be abandoned as soon as it becomes obsolete. If a new obstacle enters the threat horizon, or a known one leaves it, the search will be resumed from scratch. Eventually, a safety-preserving path to the goal will be found[1], and in the process, safety is never compromised. Such a search is described in Chapter 5.

The theoretical basis for safety-maintenance appears in Section 3.1.2.1 above. As long as objects are constrained to appear outside of the threat horizon, we know by Theorem 1 (page 16) that a safe haven exists. Corollary 1 extends this result to domains, such as Dodger, where the number of obstacles appearing over time is unbounded, and subject only to a maximum number that may be within some fixed distance of the robot at any given time. The proof of Corollary 1 also provides the fundamentals of an algorithm for avoidance. As each obstacle crosses the threat horizon, the Dodger system is faced with a choice: if no obstacle happens to be inside the safety region[2], then

[1] Recall that Corollary 3 of Section 3.4 establishes sufficient conditions for ensuring that the robot can always find a path that takes it closer to the goal than its current position.

[2] Recall that the safety region is simply a circle whose diameter is just larger than the sum of the maximum widths

Dodger computes a safe haven with respect to all of the obstacles it knows about, and it begins to head there immediately. If obstacles are inside of the safety region, then Dodger may not be able to find an unobstructed, constant-velocity path to safety. But the threat horizon was constructed to ensure that, eventually, such a path will exist. In such cases, Dodger can continue with whatever it is currently doing until the time that it finds a constant velocity path to a new safe haven. The theoretical results ensure that Dodger will be safe in any case.

This chapter describes two different methods for computing the safe haven: a deterministic one that finds the intersections of the safety region with the planks which represent the space occupied by the obstacles over time, and another which uses Monte Carlo methods to find a safe haven. The second method suffers from two defects: there is a very small but non-zero chance that it will fail to find a safe haven, even when one exists, and it requires the threat horizon to be extended somewhat. However, this technique is algorithmically simple and much more computationally efficient than the deterministic algorithm. It is the algorithm actually used in the Dodger system, and neither of its theoretical drawbacks has proven to be a difficulty in practice.

4.1 Finding a Safe Haven Deterministically

Recall that a **plank** is a pair of parallel lines in the plane. The extremes of an obstacle moving at a fixed velocity will trace two parallel rays over time. In Chapter 3 the region between these two rays was called a **half-plank**. The problem of finding a safe haven can then be posed as the problem of determining a part of the safety region that does not intersect any of the half-planks associated with the obstacles inside of the threat horizon. This section describes one way of doing this.

4.1.1 Preprocessing

In the current implementation, Dodger models obstacles in $\mathcal{C}$-space as a center point, a width (or radius), a speed, and an angle of trajectory. For the purposes of the algorithm described here, this representation needs to be converted to the two parallel lines which bound the obstacle's path in the 2-dimensional spatial plane. Secondly, the algorithm requires these lines to be segments, and not rays, so one must find an appropriate place to clip. It is possible to calculate the obstacle's location at a sufficiently distant point in time and use the segment between that point and the obstacle's initial location. However, the rest of this section assumes that we have tested each line for intersection with the safety region, and that all of the line segments which the algorithm processes lie within the safety region, with their endpoints on the circle which bounds it. While this will not improve processing in the worst-case, it both simplifies the algorithm and promises improved average-case performance in all domains where even a small number of obstacles do not intersect the safety region.

Since by definition the safety region is wider than the obstacles, if an obstacle intersects the safety region, then at least one of an obstacle's two bounding lines must intersect the circle which bounds the safety region. As long as one keeps information about which side of a given segment the obstacle is on (and thus which side it is not on), the algorithm does not need to keep track of the corresponding parallel line in the cases where only one of the two bounding rays of a half-plank intersects the safety region.

Next, obstacles must be "merged": the algorithm requires that the segments do not coincide. So, if two obstacles happen to be traveling parallel to each other, and happen to share a common outer boundary, they can be joined into a single obstacle. Similarly, if two or more obstacles happen to share a trajectory (though perhaps separated in time), or if they travel in exactly opposite directions, all but one of these obstacles can be thrown out. One way to do this would be to first

of n obstacles, where n is the largest number of obstacles that will be within the threat horizon of the robot at any given time.

"normalize" the segments so that all segments have trajectories between 0 and π as described above, and each segment is further represented by the point where its containing line crosses the y-axis (or, if it parallels the y-axis, the point where it crosses the x-axis.) These normalized segments can then be easily tested for duplicates. In the cases where coincident segments are the result of completely overlapping obstacle paths, we can throw out all but one. In cases where the coincidence is the result of two parallel obstacles that touch at a point, both of the segments can be thrown out, effectively merging the two obstacles into a single larger one. Again, these determinations can be made simply by maintaining information about which side of a segment is the "inside."

4.1.2 Data Structure

The algorithm uses what is known as a **winged-edge** data structure (8). This description closely follows 67 (67). There are three fundamental data types in this structure: vertices, edges and faces. Edges are the principle type in the following sense: each vertex points to (any) one of its incident edges. Each face also points to an arbitrary one of its edges. In contrast, each edge record e in the basic data structure contains eight pointers: one to each of its endpoints, v_0 and v_1, one to each of the two faces which contain it, f_0 and f_1, two to edges incident to e at v_0, and two to edges incident to e at v_1. Following O'Rourke, these latter edges are named ${e_0}^-, {e_0}^+, {e_1}^-$, and ${e_1}^+$, where ${e_0}^-$ is the edge incident to e at v_0 in the clockwise direction, ${e_0}^+$ is the edge incident to e in the counterclockwise direction, etc. f_0 and f_1 are such that, if one starts at e and follows the clockwise edges starting at ${e_0}^-$, the edges of f_0 will be encountered. Similarly, the edges of f_1 can be produced by following the counterclockwise edges starting with ${e_0}^+$.

This algorithm will require the use of two additional fields in the edge structure: every edge will be a part of either the circle representing the boundary of the safety region, or a ray representing the outside edge of a half-plank. Assume the half-planks will be numbered from 1 to n. The two rays of each half plank i will be assigned the numbers $2i - 1$ and $2i$, and the safety-region circle will be assigned the number 0. A field, R, is needed to hold this number, which will tell us whether an edge is a line segment ($R \neq 0$) or an arc ($R = 0$), as well as which ray the edge is associated with. Note that, after the preprocessing above, it is not possible for a single edge to be part of more than one ray (as in the case where two parallel planks touch, and their edges coincide.) In the event that an edge is part of the circle, a bit is also needed to indicate whether it is a major or minor arc of that circle. Face records are also extended to contain a field that will tell whether or not the face is on the inside or outside of a plank.

4.1.3 Algorithm

If a plank intersects a circle, it will create either 2 or 3 distinct regions, as depicted in Figure 4.1(a) and (b). Each maximally connected region of the plane, that contains no edges or vertices, is known as a **face**. The darkened area in this figure depicts the area of intersection, and the lighter area represents the part of the circle that would be a safety region with respect to this single threat. When a second plank intersects the circle, as shown in Figure 4.1(c), a number of new faces can be created. Note that while the **size** of the unshaded area decreases monotonically with each new plank, the **number** of unshaded faces can either increase or decrease when a new plank intersects some set of existing planks and the circle representing the safety region. The basic idea of the algorithm is to keep track of the areas inside the circle that are not intersected by any plank. We will "mark" all of the faces that are contained in the interior of one or more planks, so that, once the algorithm is completed, the unmarked faces will each constitute a region that is a safe haven with respect to all of the obstacles considered. Processing is done plank-by-plank, and for each plank, edge-by-edge. As each edge is added, existing edges and faces are bisected, and so new edges and faces must be created, and existing ones modified. Once both sides of the plank are processed, and the winged-edge data structure has been modified to reflect the new topology of the graph, the faces between these two plank edges are then marked, to indicate that they are