A Generalized Framework for Indexing OLAP Aggregates

Yannis Kotidis
Department of Computer Science
University of Maryland
kotidis@cs.umd.edu

Nick Roussopoulos
Department of Computer Science
and
Institute of Advanced Computer Studies
University of Maryland
nick@cs.umd.edu

October 29, 1997

Abstract

Decision support applications often require fast response time to a wide variety of aggregate queries extracted from huge amounts of data. In this paper we propose the use of well organized packed R-trees for storing and maintaining multidimensional aggregates. Moreover, we present a general framework for mapping OLAP data to a collection of R-trees that achieve a high degree of data clustering with very low space overhead. We then propose four different allocation strategies designed to optimize different application needs. On the second part of the paper we present experimental results on high dimensionality OLAP data (up to 10 dimensions) of realistic size. Finally we characterize the performance of the proposed allocation strategies with respect to both incremental updates and response time for a variety of different queries.

1 Introduction

On-line analytical processing (OLAP) , in the context of a data warehouse, typically involves hundreds of complex aggregate queries over vast amounts of data. The mere size of the data warehouse does not permit computation from the raw data each time such a query is invoked. In order to speed up processing, commercial systems pre-compute aggregate views of the base data along multiple dimensions.

The most popular way to define this aggregation procedure is the data cube operator [GBLP96]. In technical terms, the cube is a redundant multidimensional projection of a relation. It computes all possible groupby SQL operators and aggregates their results into an N-dimensional space for answering OLAP queries. These aggregates are then stored in derived summary tables whose size can be estimated using mathematical tools [SDNR96]. Because these tables are typically very large, indexing, which adds to their redundancy, is necessary to speed up queries on them. There is direct tradeoff between redundancy and performance and a rather typical optimization strategy is for a given amount of storage, to find the best selection of summary tables and indexes which maximizes query performance [Rou82, GHRU97].

However, another, and yet even more important optimization, seems to be the selection of the best type of indices for the aggregate data. Conventional indices like B-trees may not only waste a lot of storage, but also perform badly on multidimensional range queries. On the other hand, multidimensional arrays with the dimensions forming the axes of the array do not handle sparse data easily. Colliat in [Col96] states that typically about 20% of the logical cube space in non zero. To address this problem Essbase [Ear94] asks the user to specify a set of dense dimensions of the Cube. A conventional index is build on the remaining sparse dimensions having on its leaf nodes pointers to multidimensional arrays formed by the dense dimensions. Even though exact queries are handled efficiently, range queries on dimensions that are not on the outermost dimensions of the index will give poor results. Hierarchical indexing methods [JS96] work well especially for data at higher levels of aggregation, however they demand a large storage overhead with questionable update efficiency.

Bit-mapped indices and variations [OQ97, OG95] provide another means of handling sparse data. However, high cardinality data will result in extremely large bit-maps that might not behave well at all for many types of range queries. This is because the number of OR operations is proportional to the ranges covered by the queries.

R-trees [Gut84] have a number of advantages over the indexing methods discussed so far. Queries on the data cube are naturally mapped to range queries for the index. Compared to bit-maps, R-trees provide less space overhead, since they index only regions of the space that actually contain data. However performance of the R-trees is expected to suffer as the number of dimensions increases. Moreover one-at-a-time insertions not only take a lot of time but also result in poor organization of the intermediate levels of the index.

Packed R-trees [RL85] handle these problems by sorting first the points in a desirable order and then bulk loading the sorted file. They not only minimize the overlap between indexed areas but also achieve minimum space overhead as nodes are packed to capacity. In [RKR97] we proposed the use of *Cubetrees*, that is well organized packed R-trees for indexing the data cube. We now extend these ideas and propose a more general framework for mapping OLAP data to a collection of such Cubetrees. Furthermore, we characterize the properties of such mapping and propose four organizations that optimize different aspects of the mapping. We also describe an architecture for bulk incremental updates of the structure and discuss special implementation issues . Finally, we include experimental results on high dimensional data, of realistic size, with respect to different types of range queries that are common in OLAP.

2 R-trees as place holders for multidimensional aggregates

The Cube operator can be naturally visualized in a multidimensional space, where the axes define the dimensions in which the data is aggregated. The points in that space contain the selected aggregates and are located in the hyper-planes defined by the combination of attributes on which the data is grouped. In Figure 1 we can see the 3-d Cube on {`product,date,city`}. All groupby(`product,date`) aggregates are stored in the `product,date` plane.



Figure 1: The Data Cube

In [RKR97] we proposed the use of well organized packed R-trees for storing this multidimensional data. Moreover we showed that even though a single N-dim R-tree provides the necessary indexing-space for holding the whole Cube, the interleaving between the points of all hyper-planes results in poor clustering in the leaf-pages of the index. We then addressed this problem by partitioning the N-dim space into Nx(N-1)-dim sub-cubes, each realized by an R-tree and then allocating the groupby values in such a way that we avoid de-clustering of neighboring points in the leaves.



Figure 2: Indexing space within a 3-dim R-tree

We now take this process several steps further by separating any semantics information from the R-tree itself. Typically any R-tree is considered as a multidimensional index on a combination of attributes like `(store,date,item)`. In the context of this work we will treat each R-tree as a place holder for multidimensional aggregates with no semantics on its axes. Figure 2 shows the space[1] that a 3-dim R-tree can index: one 3-dim, three 2-dim and three 1-dim groupbys. By taking away the semantics from the axes, all of these hyper-planes can be used for storing aggregate data originating from relations that are not necessarily related.



Figure 3: Feasible mapping of 4 groupbys to a 3-dim R-tree

Figure 3 shows a 3-dim R-tree used for storing 4 different set of groupbys. Notice that since we impose no semantics on the R-tree itself, the axes are not "labeled" and different hyper-planes are used for

[1]We assume that each domain has been extended with a special value on which we do the projections.

placing unrelated aggregate data. What permits such a generalization is that all these hyper-planes are perpendicular with each other and therefore their corresponding points can be addressed using common spatial range queries. For example an arbitrary query on groupby(`date,zone`) on the previous example can be formulated as $< date_1, zone_1, 0, date_2, zone_2, 0 >$, where $date_i$ and $zone_i, i = 1,2$ define the query boundaries.

In general a N-dim R-tree provides space for $selections(N,i) = \frac{N!}{i!(N-i)!}$ different groupbys between i dimensions. For example an 4-dim R-tree can hold :

- one 4-dim groupby
- four 3-dim groupbys
- six 2-dim groupbys and
- four 1-dim groupbys

For the rest of this paper we will denote an N-dim R-tree by $r(a_1, a_2, \ldots, a_N)$, where a_i, i=1,..., N are the N axes. A hyper-plane in r is defined as a subset h of $\{a_1, a_2, \ldots, a_N\}$. A groupby among m dimensions will be denoted as $g(d_1, d_2, \ldots, d_m)$. In general, a set of groupbys $G = \{g_1(d_1^1, \ldots, d_{m_1}^1), g_2(d_1^2, \ldots, d_{m_2}^2) \ldots\}$ will be realized through a forest of R-trees $R = \{r_1(a_1^1, \ldots, a_{n_1}^1), r_2(a_1^2, \ldots, a_{n_2}^2) \ldots\}$ by mapping each g_i into a hyper-plane h of $r_j \in R$. If we use H to represent all different hyper-planes then this mapping can be viewed as an one-to-one function $\mathcal{F}$: $G \to H$.

The selection of $\mathcal{F}$ is the critical factor that will determine the efficiency of the mapping when maintaining and querying the forest. Given $\mathcal{F}$, for each R-tree r one should be able to determine the best sort order in which all corresponding points should be placed in the leaves of the index. A sort order s for $r(a_1, a_2, \ldots, a_n)$ is a permutation of $\{a_1, a_2, \ldots, a_n\}$. In [RKR97] we proposed an algorithm for selecting a "good" sort order within a packed R-tree. In Figure 4 we generalize that algorithm for the new extended framework.

2.1 Properties of $\mathcal{F}$

From the discussion on the previous paragraph it is clear that there is an exponential number of feasible mapping functions that can be used to realize the Data Cube. We can reduce the number of possible choices by using the following criteria :

Good Organization: There are many different ways to characterize the clustering inside the index structure. In [RKR97] we defined the term of *dispersed groupbys* for those groupbys that we can not guarantee any level of clustering at all with respect to a selected sort order. Such groupbys will have their values scattered among different leaf pages of the tree. In such cases we will need one page access for each retrieved point on query time. The minimum requirement that we can set for $g(d_1, d_2, \ldots, d_m)$ is that values of g among at least one of $d_1, d_2, \ldots, d_m$ should be placed in continuous space in the leaves of the index. This minimum requirement is enough to guarantee that at least at the leaf level of the R-tree we have values of g clustered together. Figure 5 shows the placement of the groupbys shown in Figure 3 according to the sort order returned by the `ComputeSortOrder` algorithm. We can see that in this case the minimum requirement of no dispersed groupbys is met. However there is no feasible sort order that places all groupby(`store,sales_person,zone`) values together, unless we place one of groupby(`customer,item`) and groupby(`date,zone`) on a separate R-tree. By requiring clustering among more dimensions we can get less interleaving between the values of different groupbys, at the cost of using more R-trees to store the same number of groupbys.

```
ComputeSortOrder(r, G, F) {
    for i=1 to n
      count_i = 0;
    for each hyper-plane h ∈ r
      if(used(h, G, F))
        for each a_j ∈ h
          count_j++;
    sort a_i based on count_i in increasing order;
    output sorted list of a_i;
}

boolean used(h, G, F) {
   if (∃g ∈ G : F(g)=h)
       return TRUE;
   else
       return FALSE;
}
```

Figure 4: `ComputeSortOrder`: Computes a sort order for r



Figure 5: Groupbys placement at the leaf nodes

Small size overhead: When storing $g(d_1, d_2, \ldots, d_m)$ in a hyper-plane of an N-dim R-tree, each value of g has to be converted to an N-dim point. If $N > m$ we pay an extra overhead by introducing unused coordinates (as zeros). In some cases we can avoid paying this extra cost by compressing the values of g. We will further discuss this mechanism later on.

Fast Updates: New data is added to the data warehouse through a batch process that in some cases happens during down-time. A crucial goal of every warehouse is to minimize the length of this update phase. Loading the R-trees depends on $\mathcal{F}$. It requires sorting of the increment and data conversion to the R-tree dimensionality as we already discussed. Moreover, depending on $\mathcal{F}$ we might need concurrent reads from multiple files and costly comparisons, as the sorted runs that are generated by the new increment for each $g \in G$ are merged with the existing data.

Small number of Indices: It is advantageous to use the minimum number of R-trees to realize a given set G. This would not only ease the maintenance procedure, but would also enhance query performance as successive queries to the same index will most probably find the top-level pages of that index already buffered in main memory.

Notice that not all of these criteria can be met at the same time. For example using the minimum number of indexes to gain from buffering may contradict with the goal of good organization inside them. The challenge is to find the mapping that compromises all these criteria in an optimal way.

2.2 Proposed Organizations

For the following discussion we will assume that the full Data Cube for N dimensions is to be realized. Out of the 2^N-1 possible groupbys, the groupby($none$) corresponds to a single value that can be allocated to any R-tree. We will focus on the rest 2^N-2 combinations. In most cases the generalization, where only a sub-cube out of them is chosen to be materialized, is straightforward. We will discuss four different solutions for computing the mapping function $\mathcal{F}$.

Single R-tree: In this scheme all different groupbys are allocated to a single R-tree. This selection obviously minimizes the number of indices in R.

Reduced R-trees: This scheme addresses the problem of dispersed groupbys in the previous case. As shown in [RKR97] a single R-tree will decluster half of the groupbys in the Data Cube. By doing a dimensionality reduction and using Nx(N-1)-dim R-trees we dramatically reduced the number of dispersed groupbys while keeping the number of R-trees as small as possible. Under the more general framework of mapping functions one can reorganize the N Reduced R-trees so that no groupby will be dispersed for every value of N. The algorithm shown in Figure 6 allocates G to N R-trees under the reduced scheme.

ReducedScheme(G) {
  Initialize r_i s.t $dimensionality(r_i) = N\text{-}1, i = 1, \ldots, N$;
  index=1;
  for (i=1 to N-1)
    for all $g \in G$
      if($dimensionality(g) == i$) {
        extract g from G;
        map g to a hyper-plane $h_k \in r_{index}$ that is compatible[a]
        with every other h_l already used in r_{index};
        index=(index+1) mod N;
      }
  }

[a] Two hyper-planes h_1, h_2 are compatible iff $h_1 \cap h_2 \neq \emptyset$

Figure 6: `ReducedScheme`: Allocates full cube G into a minimum set of R-trees with no dispersed groupbys